



Timbre Plus Texture

- Description:** **TIMBRE PLUS TEXTURE** is a unique water reducible, solventless oil based coating that has outstanding adhesion and toughness.
Ideal for decking, stair treads and walkways
Timbre Plus Texture incorporates textured beads to give grip to horizontal surfaces
IMPORTANT NOTE: When using transparent finishes it is most important that the correct application procedure and the right amount of material is used to obtain maximum life.
- Where to use:** Suitable for most timbers.
All timbers need to be cleaned prior to application to prevent early adhesion failure and also help with the drying time. Tannins and resins in the timber contaminate coatings hence early adhesion failure and water sensitivity.
We recommend cleaning with Quantum Sap Strip and a power wash.
If sanding is necessary use a fine grit and clean after sanding with Quantum Sap-Strip.
Refer to Quantum Decking System available on the website.
- How to apply:** The timber should be dry and free from contamination. For best results coat timber so as to achieve maximum penetration with first coat. Allow drying time of 3-4 hours for 1st coat (depending on type of timber) followed by at least 2 subsequent coats allowing drying time between coats.
- Spraying:** Airless spray recommended 13 tip, with 20⁰ to 30⁰ fan, 1000 - 1400 P.S.I tip pressure, use normal protection i.e. mask, overalls, watch your over spray! Wash off with soap and water before it dries.
- Coverage:** This will depend on the porosity of the timber; old wood may use as much as 1 litre per 4 square metres, new timber up to 1 litre per 7 square metres. At least 3 coats are recommended for optimum life.
Remember this is a saturation finish not a surface coating.
- Drying time:** Drying time is 3-4 hours @ 20°C. First coat may be slower to dry due to the extractives in the wood.
- Renewing finish:** When the surface requires re-coating, hose and dust off any dirt, apply one or two coats. Touching up weathered areas as they occur will keep your timber looking good for years. For best results wash down surface with timber cleaner and a strong jet of water to remove any old finish and sterilise any fungus and mould (dark patches in the timber). The wash down also helps to open the timber and assist in the penetration of finish. Apply as per new timber.
- Clean up:** Wash brushes and tools in soap and water.
- Environment:** Quantum Timber Finishes do not use mineral spirit products in manufacturing, hence all Quantum products are low in VOCs. **VOC <20g/litre**
The entire range is free of hazardous air pollutants (HAPS).

Horizontal timber decks are subject to the harshest weather conditions of any painted surface, plus the additional wear and tear of regular traffic. To keep your deck looking good, regular maintenance is essential.

KEEP OUT OF REACH OF CHILDREN

If swallowed, do not induce vomiting, call nearest poisons information centre.

Keep away from flame and heat. Avoid breathing spray mist.