



MIROTONE



QUANTUM
Timber Finishes

4 May 2017

Commercial-In-Confidence

Statement of VOC in Coating

The method for the determination of VOC levels of the listed products is detailed in South Coast Air Quality Management District (California, U.S.) – Rule 1136 (Wood Products Coatings)

Product	Description	VOC content
4350	MICROCLEAR (Interior)	46 g/L

Note: The VOC levels have been determined by the calculation method. The information used is based on supplier information (e.g. MSDS and Datasheet) for the ingredients and our own formulation of the coating. The VOC content above is the maximum VOC exclusive of water and exempt compounds.

This declaration is provided in good faith and the information contained herein is based on data considered accurate at the time of preparing this document. No warranty is expressed or implied regarding the accuracy of this data. This declaration is not intended in any way to be a warranty of performance or compliance to any specification, expressed or implied.

NEW SOUTH WALES
21 Marigold Street, Revesby NSW 2212
PO Box 380, Panania, NSW, 2213
Phone: +61 2 9795 3700
Fax: +61 2 9771 3601

VICTORIA
147 Ordish Road, Dandenong VIC 3175
P O Box 1071, Dandenong VIC 3175
Phone: +61 3 9706 5077
Fax: +61 3 9794 0733

QUEENSLAND
679 Progress Road, Wacol QLD 4076
PO Box 3941, Mt Ommaney QLD 4074
Phone: +61 7 3115 5200
Fax: +61 7 3271 3757