



QUANTUM

TIMBER FINISHES



Environmentally Sustainable, Environmentally Responsible.

ECODEX QUIX Decking Finish

A deeply penetrating water based oil which nourishes and protects the timber resulting in a durable, matt, natural looking finish. Designed and manufactured in Australia to protect your deck from harsh Australian conditions.

Advantages

- Fast drying, one hour recoat, replace furniture 4 hours after completion of second coat.
- No odour / low VOC.
- Durable, water resistant timber finish that will weather naturally without risk of flaking, blistering or peeling.
- Resists stains, dirt and mould helping the timber stay fresh and clean.
- Water repellent minimises cracking and splitting of the timber by creating a protective barrier that reduces water penetration.
- Environmentally responsible - made from bio-based, ecologically sustainable products.

Typical Applications

Exterior decking.

Coverage

- 10-14m² per litre depending upon the porosity of the timber. First coat may use more than subsequent coats.

Application Method

By brush, roller or applicator.

Surface Preparation: Good preparation is key to a professional looking, long lasting finish. All timber should be cleaned prior to application to prevent early adhesion failure:

- **New Timber:** Clean with SAP STRIP prior to coating to remove all tannins, extractives & mill glaze and assist with opening the timber grain.
- **Weathered, Grey or Dirty Timber:** Clean with DEX PREP prior to coating to remove all dirt and weathered fibres.
- **Previously Stained or Oiled Timber:** Test the water repellency of the timber by dripping beads onto the surface, if the timber absorbs the water, clean with DEX PREP and then coat. If water beads on the

ECODEX QUIX



A deeply penetrating water based oil which nourishes and protects the timber resulting in a durable, matt, natural looking finish. Designed and manufactured in Australia to protect your deck from harsh Australian conditions.

surface, clean with POWER CLEAN first to remove weathered oil finishes, then clean with DEX PREP to neutralise and lighten the timber before coating.

- **Previously Painted Timber:** Sand back or use Q-STRIP to remove all old paint, finish with a pressure wash.
1. After cleaning (see above), spray a light mist of water over the deck prior to coating to help ECODEX QUIX to penetrate the timber.
 2. Stir ECODEX QUIX thoroughly with a broad flat paddle before and during application.
 3. Using a brush, roller, applicator or spray, apply ECODEX QUIX liberally along the length of the boards. Coat no more than 2 to 3 boards at a time to maintain a wet edge and prevent lap marks.
 4. After 1-hour dry time, apply a second coat.
 5. If desired a third coat may be applied. (Note: the second coat may be slightly slower drying so a 2 hour recoat is recommended).

Specifications	Heat/Temperature	Do not apply if temperature is below 15°C or above 30°C. Do not apply in full sun or when rain or heavy dew is expected within 36 hours.
	Drying	Recoat – 1 hour Replace Furniture – 4 hours <i>In cooler or humid conditions drying times will be longer.</i>
Properties	Colour	Available in a lightly pigmented natural colour to provide a natural looking finish. It may also be tinted to highlight the characteristics of common Australian timbers.
	Finish	Matt.
	VOC Level	<38g/L.
	Thinner	Not Required.
	Pack Sizes	4L, 10L. (6L promo only)
	Product Code	4720.
	Clean Up	Water clean-up.

Health & Safety

Before handling, refer to the Safety Data Sheet (SDS) for health and safety information. Ensure that all people using this product have read and understood this data sheet, the associated SDS and packaging label before using this product.