

ECODEX QUIX Decking Finish

A deeply penetrating water based oil which nourishes and protects the timber resulting in a durable, matt, natural looking finish. Designed and manufactured in Australia to protect your timber deck from harsh Australian conditions.

Product Advantages

- Fast drying, one hour recoat, replace furniture 4 hours after completion of second coat
- No odour / low VOC
- Durable, water resistant timber finish that will weather naturally without risk of flaking, blistering or peeling
- Resists stains, dirt and mould helping the timber stay fresh and clean
- Water repellent minimises cracking and splitting of the timber by creating a protective barrier that reduces water penetration
- Environmentally responsible - made from bio-based, ecologically sustainable products

Typical Applications

Exterior decking.

Typical Properties

Colour: Available in a lightly pigmented natural colour to provide a natural looking finish. It may also be tinted to highlight the characteristics of common Australian timbers.

Gloss: Matt

VOC: <38 g per litre

Coverage: 10-14m² per litre depending on the porosity of the timber. First coat will use more than subsequent coats.

Application Methods: Brush, roller, spray or applicator.

Surface Preparation: Good preparation is key to a professional looking, long lasting finish. All timber should be cleaned prior to application to prevent early adhesion failure:

- **New Timber:** Clean with SAP STRIP prior to coating to remove dirt and assist with opening the timber grain.
- **Weathered, Grey or Dirty Timber:** Clean with DEX PREP prior to coating to remove all tannins, extractives and mill glaze.
- **Previously Stained or Oiled Timber:** Test the water repellency of the timber by dripping beads onto the surface, if the timber absorbs the water, clean with DEX PREP and then coat. If water beads on the surface, clean with POWER CLEAN first to remove weathered oil finishes, then clean with DEX PREP to neutralise and lighten the timber before coating.
- **Previously Painted Timber:** Sand back or use Q-STRIP to remove all old paint, finish with a pressure wash.

Application:

1. After cleaning (refer to surface preparation), spray a light mist of water over the deck prior to coating to help ECODEX QUIX to penetrate the timber.

2. Stir ECODEX QUIX thoroughly with a broad flat paddle before and during application.
3. Using a brush, roller, applicator or spray, apply ECODEX QUIX liberally along the length of the boards. Coat no more than 2 to 3 boards at a time to maintain a wet edge and prevent lap marks.
4. After 1-hour dry time, apply a second coat.
5. If desired a third coat may be applied. (Note: the second coat may be slightly slower drying so a 2 hour recoat is recommended).

Drying: Recoat: One hour Replace Furniture 4 hours

In cooler or humid conditions drying times will be longer. Do not apply if temperature is below 15°C or above 30°C. Do not apply in full sun or when rain or heavy dew is expected within 36 hours.

Clean Up: Clean all equipment using water.

Product Code: 4720

Packaging: 4L, 10L (6L promo only)

Health & Safety

Before handling, refer to the Safety Data Sheet (SDS) for health and safety information. Ensure that all people using this product have read and understood this data sheet, the associated SDS and packaging label before using this product.