

## E.L. DECKCOAT

A non-slip, opaque solid colour decking finish.

### Product Advantages

- Environmentally responsible - made from bio based, ecologically sustainable products.
- Non-toxic, low odour
- Self-priming, fills minor surface checks without concealing too much of the surface texture.
- Fast drying and easy to use.
- Non slip for added safety.

### Typical Applications

Older weathered decking and decking that is difficult to maintain such as holiday homes or when annual maintenance is unrealistic.

### Typical Properties

Colour: Tinted to one of Quantum's Solid Opaque Stains

Gloss: Matt

VOC: <57 g per litre

**Coverage:** 10-14 m<sup>2</sup> per litre, first coat may use more depending upon the porosity of the timber.

**Thinning:** In hot weather thin up to 5% with water or Quantum Wet Edge Extender

**Application Methods:** Brush, roller or spray

Good preparation is key to a professional looking, long lasting finish:

- New timber – power wash using SAP STRIP to remove all extractives and sterilise any fungus or mould. This will also help open up the timber and remove mill glaze to assist with penetration of the coating.
- Old timber – Wash with DEX PREP and a strong jet of water to rid the surface of oxidisation (greying). Test adhesion in a small area.
- Apply a minimum of 2 coats, use 3 coats on porous surfaces.
- Spraying: Airless spray recommended. Use a 0.33 to 0.38mm (13 – 15 thou) orifice, 10cm fan (dependent on job) with a regulated pump pressure of 350-400 kPa (50 – 55 psi) tip pressure. Back brushing is recommended to achieve an even finish. Use normal protection i.e. mask, overalls. Watch your overspray. Wash off with soap and water before it dries

Recoating: The timber will grey off if not recoated every 6-9 months, however the protective properties will still remain in the timber.

**Drying:** Touch Dry – 30 minutes                      Recoat – 2 hours

*In cooler or humid conditions drying times will be longer. Do not apply if temperature is below 12°C or above 30°C*

**Clean Up:** Clean all equipment using water.

**Product Code:** 4790

**Packaging:** 4L & 10L

## **Health & Safety**

Before handling, refer to the Safety Data Sheet (SDS) for health and safety information. Ensure that all people using this product have read and understood this data sheet, the associated SDS and packaging label before using this product.

The information in this data sheet represents typical values. Application variables affect product performance therefore this information should be used as a guide. The user must satisfy themselves as to the suitability of this product for their requirements. Mirotone assumes no liability for use of this information.