



GOLD

A premium exterior, transparent, penetrating timber finish, to enhance the natural grain and hues of timber without concealing them. Final undertones tend towards a reddish gold.

Product Advantages

- Environmentally responsible - made from bio based, ecologically sustainable products.
- Non-toxic, low odour.
- Water repellent, helps to prevent the swelling and shrinking of the timber that causes cracking and splintering.
- UV resistant, contains UV absorbers.
- Mildew and fungal resistant.
- Touch up weathered areas as they occur, no need for a full recoat.

Typical Applications

Softwood - Exterior timber such as Cedar, Cypress, Oregon and treated pine. Excellent on broad surface areas and outdoor furniture.

Typical Properties

Colour: Golden
Gloss: Low Sheen
VOC: <144 g per litre

Coverage: Old timber may use up to 1 litre per 2 m².
New timber may use up to 1 litre per 7 m² per litre, first coat may use more depending upon the porosity of the timber.

Note: Gold is a saturation finish, not a surface coating.

Application Methods: Brush, roller (short nap) or spray

Good preparation is key to a professional looking, long lasting finish:

- New timber – power wash using SAP STRIP to remove all extractives and sterilise any fungus or mould. This will also help open up the timber and remove mill glaze to assist with penetration of the coating.
 - Old timber – Wash with DEX PREP and a strong jet of water to rid the surface of oxidisation (greying). Test adhesion in a small area.
 - Apply the first coat liberally to allow penetration, allow to dry.
 - Apply two more coats, allow 24 hour dry time between coats.
- Spraying: Airless spray recommended. Use a 0.33 to 0.38mm (13 – 15 thou) orifice, 10cm fan (dependent on job) with a regulated pump pressure of 350-400 kPa (50 – 55 psi) tip pressure. Back brushing is recommended to achieve an even finish. Use normal protection i.e. mask, overalls. Watch your overspray. Wash off with soap and water before it dries.

Renewing finish – hose off dust, dirt or salt. Apply one good coat. If coating has eroded back to bare timber then a timber cleaner will be required.

Drying: Touch Dry – 12-24 hours Recoat – 24 hours
In cooler or humid conditions drying times will be longer. Do not apply if temperature is below 15°C or above 30°C

Clean Up: Clean all equipment using water.

Product Code: 4570

Packaging: 1L, 4L, 10L & 20L

Health & Safety

Before handling, refer to the Safety Data Sheet (SDS) for health and safety information. Ensure that all people using this product have read and understood this data sheet, the associated SDS and packaging label before using this product.