

QSTRIP

A bio-degradable paint remover that cleans up in water.

Product Advantages

- No strong caustic chemicals.
- Removes coating without adversely affecting the underlying timber.
- Will remove most conventional coatings.

Typical Applications

Designed for wood but may be applied to glass, metal, concrete, plaster or masonry.

Coverage: 2.5m² per litre

Application Methods:

- The removal process depends upon the type of coating and the number of coats that are being removed.
- Test a small area prior to application to determine the thickness of the QSTRIP required and the time needed to allow it to work.
- Generally two applications will work, however sometimes a third application may be required.
- Leave QSTRIP for a minimum of 40 minutes to soften and dissolve the film. Thicker coatings may take a few hours.
- On stubborn coatings use a stiff broom or brush, (pay close attention to cracks and grooves), then remove by scraping, scrubbing or power wash.
- When the film is completely removed wash with water and then allow to dry.

Precautions:

- Not to be used on plastic surfaces.
- Do not use if rain is forecast.
- Do not allow to dry out.

Clean Up: Clean all equipment using water.

Product Code: 4925

Packaging: 1L, 4L & 10L

Health & Safety

Before handling, refer to the Safety Data Sheet (SDS) for health and safety information. Ensure that all people using this product have read and understood this data sheet, the associated SDS and packaging label before using this product.