

# MICROFLOOR - gloss levels

## Mirotone (Mirotone (NZ))

Chemwatch Hazard Alert Code: 2

Chemwatch: 84-9256  
Version No: 2.1.1.1  
Safety Data Sheet according to HSNO Regulations

Issue Date: 01/09/2017  
Print Date: 01/09/2017  
L.GHS.NZLEN

## SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

### Product Identifier

|                               |   |
|-------------------------------|---|
| Product name                  | MICROFLOOR - gloss levels   |
| Synonyms                      | MICROFLOOR MATT, MICROFLOOR SATIN, MICROFLOOR GLOSS, 4370-1, 4370-3, 4370-9, Product Code: 4370-1, 4370-3, 4370-9 |
| Other means of identification | Not Available   |

### Relevant identified uses of the substance or mixture and uses advised against

|                          |  |
|--------------------------|--|
| Relevant identified uses | For full details on application and properties consult the technical datasheet |
|--------------------------|--|

### Details of the supplier of the safety data sheet

| Registered company name | Mirotone (Mirotone (NZ))   | Quantum Timber Finishes                       | Mirotone                                      |
|-------------------------|--|---|---|
| Address                 | 32 Cryers Road East Tamaki, Manukau Auckland<br>2163 New Zealand | 147 Ordish Road, Dandenong Vic 3175 Australia | 21 Marigold Street Revesby NSW 2212 Australia |
| Telephone               | 0800 FINISH (0800 34 64 74)                                      | +61 2 9795 3700                               | +61 2 9795 3700                               |
| Fax                     | 0800 34 64 34  | 1300 132 202                                  | +61 2 9771 3601                               |
| Website                 | www.mirotone.co.nz   | www.qtf.com.au                                | www.mirotone.com, www.polycure.com.au         |
| Email                   | Not Available  | Not Available                                 | Not Available                                 |

### Emergency telephone number

|                                   |                                  |               |                                 |
|-----------------------------------|----------------------------------|---------------|---------------------------------|
| Association / Organisation        | Not Available                    | Not Available | Not Available                   |
| Emergency telephone numbers       | 1800 039 008 (Aust)              | Not Available | 1800 039 008 (Aust)             |
| Other emergency telephone numbers | + 61 3 9573 3112 (International) | Not Available | +61 3 9573 3112 (International) |

## SECTION 2 HAZARDS IDENTIFICATION

### Classification of the substance or mixture

**Considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Not regulated for transport of Dangerous Goods.**

### CHEMWATCH HAZARD RATINGS

|              | Min | Max |              |
|--------------|-----|-----|--------------|
| Flammability | 0   |     |              |
| Toxicity     | 1   |     | 0 = Minimum  |
| Body Contact | 2   |     | 1 = Low      |
| Reactivity   | 0   |     | 2 = Moderate |
| Chronic      | 0   |     | 3 = High     |
|              |     |     | 4 = Extreme  |

|   |  |
|---|--|
| Classification <sup>[1]</sup>                   | Acute Toxicity (Oral) Category 5, Acute Toxicity (Inhalation) Category 5, Skin Corrosion/Irritation Category 3, Eye Irritation Category 2B |
| Legend:   | 1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI       |
| Determined by Chemwatch using GHS/HSNO criteria | 6.1E (inhalation), 6.1E (oral), 6.3B, 6.4A (mild)  |

### Label elements

|                     |                |
|---------------------|----------------|
| Hazard pictogram(s) | Not Applicable |
|---------------------|----------------|

|             |                |
|-------------|----------------|
| SIGNAL WORD | <b>WARNING</b> |
|-------------|----------------|

### Hazard statement(s)

|      |                              |
|------|------------------------------|
| H303 | May be harmful if swallowed. |
| H333 | May be harmful if inhaled    |
| H316 | Causes mild skin irritation  |
| H320 | Causes eye irritation.       |

Continued...

## MICROFLOOR - gloss levels

### Supplementary statement(s)

Not Applicable

### CLP classification (additional)

Not Applicable

### Precautionary statement(s) Prevention

|             |   |
|-------------|---|
| <b>P264</b> | Wash all exposed external body areas thoroughly after handling. |
|-------------|---|

### Precautionary statement(s) Response

|                       |  |
|-----------------------|--|
| <b>P304+P312</b>      | IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.   |
| <b>P305+P351+P338</b> | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| <b>P332+P313</b>      | If skin irritation occurs: Get medical advice/attention.   |
| <b>P337+P313</b>      | If eye irritation persists: Get medical advice/attention.  |

### Precautionary statement(s) Storage

Not Applicable

### Precautionary statement(s) Disposal

Not Applicable

## SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

### Substances

See section below for composition of Mixtures

### Mixtures

| CAS No        | %[weight] | Name   |
|---------------|-----------|--|
| Not Available | 10-30     | resins   |
| 34590-94-8    | <2        | <u>dipropylene glycol monomethyl ether</u>               |
| 112-34-5      | <2        | <u>diethylene glycol monobutyl ether</u>                 |
| 121-44-8      | <2        | <u>triethylamine</u>                                     |
| 41556-26-7    | <0.2      | <u>bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate</u>    |
| 104810-47-1   | <0.2      | <u>Tinuvin 1130</u>                                      |
| 104810-48-2   | <0.2      | <u>Tinuvin 213</u>                                       |
| 82919-37-7    | <0.1      | <u>methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate</u> |
|               | balance   | Ingredients determined not to be hazardous               |

## SECTION 4 FIRST AID MEASURES

NZ Poisons Centre 0800 POISON (0800 764 766) | NZ Emergency Services: 111

### Description of first aid measures

|                     |  |
|---------------------|--|
| <b>Eye Contact</b>  | <p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Wash out immediately with fresh running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>  |
| <b>Skin Contact</b> | <p>If skin contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately remove all contaminated clothing, including footwear.</li> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul>  |
| <b>Inhalation</b>   | <ul style="list-style-type: none"> <li>▶ If fumes or combustion products are inhaled remove from contaminated area.</li> <li>▶ Lay patient down. Keep warm and rested.</li> <li>▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>▶ Transport to hospital, or doctor.</li> </ul>                      |
| <b>Ingestion</b>    | <ul style="list-style-type: none"> <li>▶ <b>If swallowed do NOT induce vomiting.</b></li> <li>▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>▶ Observe the patient carefully.</li> <li>▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>▶ Seek medical advice.</li> </ul> |

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5 FIREFIGHTING MEASURES

### Extinguishing media

Continued...

## MICROFLOOR - gloss levels

The product contains a substantial proportion of water, therefore there are no restrictions on the type of extinguishing media which may be used. Choice of extinguishing media should take into account surrounding areas.

Though the material is non-combustible, evaporation of water from the mixture, caused by the heat of nearby fire, may produce floating layers of combustible substances.

In such an event consider:

- ▶ foam.
- ▶ dry chemical powder.
- ▶ carbon dioxide.

### Special hazards arising from the substrate or mixture

|                             |             |
|-----------------------------|-------------|
| <b>Fire Incompatibility</b> | None known. |
|-----------------------------|-------------|

### Advice for firefighters

|                              |  |
|------------------------------|--|
| <b>Fire Fighting</b>         | <ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear breathing apparatus plus protective gloves in the event of a fire.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water courses.</li> <li>▶ Use fire fighting procedures suitable for surrounding area.</li> <li>▶ <b>DO NOT</b> approach containers suspected to be hot.</li> <li>▶ Cool fire exposed containers with water spray from a protected location.</li> <li>▶ If safe to do so, remove containers from path of fire.</li> <li>▶ Equipment should be thoroughly decontaminated after use.</li> </ul>  |
| <b>Fire/Explosion Hazard</b> | <ul style="list-style-type: none"> <li>▶ The material is not readily combustible under normal conditions.</li> <li>▶ However, it will break down under fire conditions and the organic component may burn.</li> <li>▶ Not considered to be a significant fire risk.</li> <li>▶ Heat may cause expansion or decomposition with violent rupture of containers.</li> <li>▶ Decomposes on heating and may produce toxic fumes of carbon monoxide (CO).</li> <li>▶ May emit acrid smoke.</li> </ul> <p>Decomposes on heating and produces toxic fumes of:</p> <ul style="list-style-type: none"> <li>, carbon dioxide (CO<sub>2</sub>)</li> <li>, nitrogen oxides (NO<sub>x</sub>)</li> <li>, other pyrolysis products typical of burning organic material.</li> </ul> <p>May emit poisonous fumes.<br/>May emit corrosive fumes.</p> |

## SECTION 6 ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

See section 8

### Environmental precautions

See section 12

### Methods and material for containment and cleaning up

| <b>Minor Spills</b>                | <ul style="list-style-type: none"> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid breathing vapours and contact with skin and eyes.</li> <li>▶ Control personal contact with the substance, by using protective equipment.</li> <li>▶ Contain and absorb spill with sand, earth, inert material or vermiculite.</li> <li>▶ Wipe up.</li> <li>▶ Place in a suitable, labelled container for waste disposal.</li> </ul>   |              |            |                 |            |             |                           |  |  |  |  |                                    |   |  |        |          |                               |   |  |       |            |                     |   |  |       |               |                            |   |  |       |         |                            |   |  |        |         |                       |   |  |       |               |                            |  |  |  |  |                                    |   |  |        |         |                               |   |  |       |            |                            |   |  |        |         |                             |   |  |        |            |                                |   |  |        |                 |                     |   |  |       |         |
|------------------------------------|--|--------------|------------|-----------------|------------|-------------|---------------------------|--|--|--|--|------------------------------------|---|--|--------|----------|-------------------------------|---|--|-------|------------|---------------------|---|--|-------|---------------|----------------------------|---|--|-------|---------|----------------------------|---|--|--------|---------|-----------------------|---|--|-------|---------------|----------------------------|--|--|--|--|------------------------------------|---|--|--------|---------|-------------------------------|---|--|-------|------------|----------------------------|---|--|--------|---------|-----------------------------|---|--|--------|------------|--------------------------------|---|--|--------|-----------------|---------------------|---|--|-------|---------|
| <b>Major Spills</b>                | <p>Chemical Class: aliphatic hydrocarbons<br/>For release onto land: recommended sorbents listed in order of priority.</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 30%;">SORBENT TYPE</th> <th style="width: 10%;">RANK</th> <th style="width: 30%;">APPLICATION</th> <th style="width: 10%;">COLLECTION</th> <th style="width: 20%;">LIMITATIONS</th> </tr> </thead> <tbody> <tr> <td colspan="5"><b>LAND SPILL - SMALL</b></td> </tr> <tr> <td>cross-linked polymer - particulate</td> <td>1</td> <td></td> <td>shovel</td> <td>R, W, SS</td> </tr> <tr> <td>cross-linked polymer - pillow</td> <td>1</td> <td></td> <td>throw</td> <td>R, DGC, RT</td> </tr> <tr> <td>wood fiber - pillow</td> <td>2</td> <td></td> <td>throw</td> <td>R, P, DGC, RT</td> </tr> <tr> <td>treated wood fibre- pillow</td> <td>2</td> <td></td> <td>throw</td> <td>DGC, RT</td> </tr> <tr> <td>sorbent clay - particulate</td> <td>3</td> <td></td> <td>shovel</td> <td>R, I, P</td> </tr> <tr> <td>foamed glass - pillow</td> <td>3</td> <td></td> <td>throw</td> <td>R, P, DGC, RT</td> </tr> <tr> <td colspan="5"><b>LAND SPILL - MEDIUM</b></td> </tr> <tr> <td>cross-linked polymer - particulate</td> <td>1</td> <td></td> <td>blower</td> <td>R,W, SS</td> </tr> <tr> <td>cross-linked polymer - pillow</td> <td>2</td> <td></td> <td>throw</td> <td>R, DGC, RT</td> </tr> <tr> <td>sorbent clay - particulate</td> <td>3</td> <td></td> <td>blower</td> <td>R, I, P</td> </tr> <tr> <td>polypropylene - particulate</td> <td>3</td> <td></td> <td>blower</td> <td>W, SS, DGC</td> </tr> <tr> <td>expanded mineral - particulate</td> <td>4</td> <td></td> <td>blower</td> <td>R, I, W, P, DGC</td> </tr> <tr> <td>polypropylene - mat</td> <td>4</td> <td></td> <td>throw</td> <td>DGC, RT</td> </tr> </tbody> </table> | SORBENT TYPE | RANK       | APPLICATION     | COLLECTION | LIMITATIONS | <b>LAND SPILL - SMALL</b> |  |  |  |  | cross-linked polymer - particulate | 1 |  | shovel | R, W, SS | cross-linked polymer - pillow | 1 |  | throw | R, DGC, RT | wood fiber - pillow | 2 |  | throw | R, P, DGC, RT | treated wood fibre- pillow | 2 |  | throw | DGC, RT | sorbent clay - particulate | 3 |  | shovel | R, I, P | foamed glass - pillow | 3 |  | throw | R, P, DGC, RT | <b>LAND SPILL - MEDIUM</b> |  |  |  |  | cross-linked polymer - particulate | 1 |  | blower | R,W, SS | cross-linked polymer - pillow | 2 |  | throw | R, DGC, RT | sorbent clay - particulate | 3 |  | blower | R, I, P | polypropylene - particulate | 3 |  | blower | W, SS, DGC | expanded mineral - particulate | 4 |  | blower | R, I, W, P, DGC | polypropylene - mat | 4 |  | throw | DGC, RT |
| SORBENT TYPE                       | RANK   | APPLICATION  | COLLECTION | LIMITATIONS     |            |             |                           |  |  |  |  |                                    |   |  |        |          |                               |   |  |       |            |                     |   |  |       |               |                            |   |  |       |         |                            |   |  |        |         |                       |   |  |       |               |                            |  |  |  |  |                                    |   |  |        |         |                               |   |  |       |            |                            |   |  |        |         |                             |   |  |        |            |                                |   |  |        |                 |                     |   |  |       |         |
| <b>LAND SPILL - SMALL</b>          |  |              |            |                 |            |             |                           |  |  |  |  |                                    |   |  |        |          |                               |   |  |       |            |                     |   |  |       |               |                            |   |  |       |         |                            |   |  |        |         |                       |   |  |       |               |                            |  |  |  |  |                                    |   |  |        |         |                               |   |  |       |            |                            |   |  |        |         |                             |   |  |        |            |                                |   |  |        |                 |                     |   |  |       |         |
| cross-linked polymer - particulate | 1  |              | shovel     | R, W, SS        |            |             |                           |  |  |  |  |                                    |   |  |        |          |                               |   |  |       |            |                     |   |  |       |               |                            |   |  |       |         |                            |   |  |        |         |                       |   |  |       |               |                            |  |  |  |  |                                    |   |  |        |         |                               |   |  |       |            |                            |   |  |        |         |                             |   |  |        |            |                                |   |  |        |                 |                     |   |  |       |         |
| cross-linked polymer - pillow      | 1  |              | throw      | R, DGC, RT      |            |             |                           |  |  |  |  |                                    |   |  |        |          |                               |   |  |       |            |                     |   |  |       |               |                            |   |  |       |         |                            |   |  |        |         |                       |   |  |       |               |                            |  |  |  |  |                                    |   |  |        |         |                               |   |  |       |            |                            |   |  |        |         |                             |   |  |        |            |                                |   |  |        |                 |                     |   |  |       |         |
| wood fiber - pillow                | 2  |              | throw      | R, P, DGC, RT   |            |             |                           |  |  |  |  |                                    |   |  |        |          |                               |   |  |       |            |                     |   |  |       |               |                            |   |  |       |         |                            |   |  |        |         |                       |   |  |       |               |                            |  |  |  |  |                                    |   |  |        |         |                               |   |  |       |            |                            |   |  |        |         |                             |   |  |        |            |                                |   |  |        |                 |                     |   |  |       |         |
| treated wood fibre- pillow         | 2  |              | throw      | DGC, RT         |            |             |                           |  |  |  |  |                                    |   |  |        |          |                               |   |  |       |            |                     |   |  |       |               |                            |   |  |       |         |                            |   |  |        |         |                       |   |  |       |               |                            |  |  |  |  |                                    |   |  |        |         |                               |   |  |       |            |                            |   |  |        |         |                             |   |  |        |            |                                |   |  |        |                 |                     |   |  |       |         |
| sorbent clay - particulate         | 3  |              | shovel     | R, I, P         |            |             |                           |  |  |  |  |                                    |   |  |        |          |                               |   |  |       |            |                     |   |  |       |               |                            |   |  |       |         |                            |   |  |        |         |                       |   |  |       |               |                            |  |  |  |  |                                    |   |  |        |         |                               |   |  |       |            |                            |   |  |        |         |                             |   |  |        |            |                                |   |  |        |                 |                     |   |  |       |         |
| foamed glass - pillow              | 3  |              | throw      | R, P, DGC, RT   |            |             |                           |  |  |  |  |                                    |   |  |        |          |                               |   |  |       |            |                     |   |  |       |               |                            |   |  |       |         |                            |   |  |        |         |                       |   |  |       |               |                            |  |  |  |  |                                    |   |  |        |         |                               |   |  |       |            |                            |   |  |        |         |                             |   |  |        |            |                                |   |  |        |                 |                     |   |  |       |         |
| <b>LAND SPILL - MEDIUM</b>         |  |              |            |                 |            |             |                           |  |  |  |  |                                    |   |  |        |          |                               |   |  |       |            |                     |   |  |       |               |                            |   |  |       |         |                            |   |  |        |         |                       |   |  |       |               |                            |  |  |  |  |                                    |   |  |        |         |                               |   |  |       |            |                            |   |  |        |         |                             |   |  |        |            |                                |   |  |        |                 |                     |   |  |       |         |
| cross-linked polymer - particulate | 1  |              | blower     | R,W, SS         |            |             |                           |  |  |  |  |                                    |   |  |        |          |                               |   |  |       |            |                     |   |  |       |               |                            |   |  |       |         |                            |   |  |        |         |                       |   |  |       |               |                            |  |  |  |  |                                    |   |  |        |         |                               |   |  |       |            |                            |   |  |        |         |                             |   |  |        |            |                                |   |  |        |                 |                     |   |  |       |         |
| cross-linked polymer - pillow      | 2  |              | throw      | R, DGC, RT      |            |             |                           |  |  |  |  |                                    |   |  |        |          |                               |   |  |       |            |                     |   |  |       |               |                            |   |  |       |         |                            |   |  |        |         |                       |   |  |       |               |                            |  |  |  |  |                                    |   |  |        |         |                               |   |  |       |            |                            |   |  |        |         |                             |   |  |        |            |                                |   |  |        |                 |                     |   |  |       |         |
| sorbent clay - particulate         | 3  |              | blower     | R, I, P         |            |             |                           |  |  |  |  |                                    |   |  |        |          |                               |   |  |       |            |                     |   |  |       |               |                            |   |  |       |         |                            |   |  |        |         |                       |   |  |       |               |                            |  |  |  |  |                                    |   |  |        |         |                               |   |  |       |            |                            |   |  |        |         |                             |   |  |        |            |                                |   |  |        |                 |                     |   |  |       |         |
| polypropylene - particulate        | 3  |              | blower     | W, SS, DGC      |            |             |                           |  |  |  |  |                                    |   |  |        |          |                               |   |  |       |            |                     |   |  |       |               |                            |   |  |       |         |                            |   |  |        |         |                       |   |  |       |               |                            |  |  |  |  |                                    |   |  |        |         |                               |   |  |       |            |                            |   |  |        |         |                             |   |  |        |            |                                |   |  |        |                 |                     |   |  |       |         |
| expanded mineral - particulate     | 4  |              | blower     | R, I, W, P, DGC |            |             |                           |  |  |  |  |                                    |   |  |        |          |                               |   |  |       |            |                     |   |  |       |               |                            |   |  |       |         |                            |   |  |        |         |                       |   |  |       |               |                            |  |  |  |  |                                    |   |  |        |         |                               |   |  |       |            |                            |   |  |        |         |                             |   |  |        |            |                                |   |  |        |                 |                     |   |  |       |         |
| polypropylene - mat                | 4  |              | throw      | DGC, RT         |            |             |                           |  |  |  |  |                                    |   |  |        |          |                               |   |  |       |            |                     |   |  |       |               |                            |   |  |       |         |                            |   |  |        |         |                       |   |  |       |               |                            |  |  |  |  |                                    |   |  |        |         |                               |   |  |       |            |                            |   |  |        |         |                             |   |  |        |            |                                |   |  |        |                 |                     |   |  |       |         |

Continued...

## MICROFLOOR - gloss levels

- Legend  
 DGC: Not effective where ground cover is dense  
 R: Not reusable  
 I: Not incinerable  
 P: Effectiveness reduced when rainy  
 RT: Not effective where terrain is rugged  
 SS: Not for use within environmentally sensitive sites  
 W: Effectiveness reduced when windy  
 Reference: Sorbents for Liquid Hazardous Substance Cleanup and Control;  
 R.W Melvold et al: Pollution Technology Review No. 150: Noyes Data Corporation 1988  
 Moderate hazard.
- ▶ Clear area of personnel and move upwind.
  - ▶ Alert Fire Brigade and tell them location and nature of hazard.
  - ▶ Wear breathing apparatus plus protective gloves.
  - ▶ Prevent, by any means available, spillage from entering drains or water course.
  - ▶ Stop leak if safe to do so.
  - ▶ Contain spill with sand, earth or vermiculite.
  - ▶ Collect recoverable product into labelled containers for recycling.
  - ▶ Neutralise/decontaminate residue (see Section 13 for specific agent).
  - ▶ Collect solid residues and seal in labelled drums for disposal.
  - ▶ Wash area and prevent runoff into drains.
  - ▶ After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.
  - ▶ If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 HANDLING AND STORAGE

## Precautions for safe handling

|                          |   |
|--------------------------|---|
| <b>Safe handling</b>     | <ul style="list-style-type: none"> <li>▶ <b>DO NOT allow clothing wet with material to stay in contact with skin</b></li> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> <li>▶ Use in a well-ventilated area.</li> <li>▶ Prevent concentration in hollows and sumps.</li> <li>▶ <b>DO NOT enter confined spaces until atmosphere has been checked.</b></li> <li>▶ <b>DO NOT allow material to contact humans, exposed food or food utensils.</b></li> <li>▶ Avoid contact with incompatible materials.</li> <li>▶ <b>When handling, DO NOT eat, drink or smoke.</b></li> <li>▶ Keep containers securely sealed when not in use.</li> <li>▶ Avoid physical damage to containers.</li> <li>▶ Always wash hands with soap and water after handling.</li> <li>▶ Work clothes should be laundered separately. Launder contaminated clothing before re-use.</li> <li>▶ Use good occupational work practice.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.</li> </ul> |
| <b>Other information</b> | <ul style="list-style-type: none"> <li>▶ Store in original containers.</li> <li>▶ Keep containers securely sealed.</li> <li>▶ Store in a cool, dry, well-ventilated area.</li> <li>▶ Store away from incompatible materials and foodstuff containers.</li> <li>▶ Protect containers against physical damage and check regularly for leaks.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> </ul>   |

## Conditions for safe storage, including any incompatibilities

|                                |   |
|--------------------------------|---|
| <b>Suitable container</b>      | <ul style="list-style-type: none"> <li>▶ Polyethylene or polypropylene container.</li> <li>▶ Packing as recommended by manufacturer.</li> <li>▶ Check all containers are clearly labelled and free from leaks.</li> </ul> |
| <b>Storage incompatibility</b> | None known  |

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

## Control parameters

## OCCUPATIONAL EXPOSURE LIMITS (OEL)

## INGREDIENT DATA

| Source   | Ingredient                          | Material name                   | TWA                             | STEL                            | Peak          | Notes                    |
|--|-------------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------|--------------------------|
| New Zealand Workplace Exposure Standards (WES) | dipropylene glycol monomethyl ether | Dipropylene glycol methyl ether | 606 mg/m <sup>3</sup> / 100 ppm | 909 mg/m <sup>3</sup> / 150 ppm | Not Available | (skin) - Skin absorption |
| New Zealand Workplace Exposure Standards (WES) | triethylamine                       | Triethylamine                   | 12 mg/m <sup>3</sup> / 3 ppm    | 20 mg/m <sup>3</sup> / 5 ppm    | Not Available | (skin) - Skin absorption |

## EMERGENCY LIMITS

| Ingredient                          | Material name   | TEEL-1  | TEEL-2   | TEEL-3    |
|-------------------------------------|---|---------|----------|-----------|
| dipropylene glycol monomethyl ether | Dipropylene glycol methyl ether                                 | 150 ppm | 1700 ppm | 9900 ppm  |
| diethylene glycol monobutyl ether   | Butoxyethoxyethanol, 2-(2-; (Diethylene glycol monobutyl ether) | 30 ppm  | 33 ppm   | 200 ppm   |
| triethylamine                       | Triethylamine   | 1 ppm   | 170 ppm  | 1,000 ppm |

| Ingredient | Original IDLH | Revised IDLH |
|------------|---------------|--------------|
|            |               |              |

## MICROFLOOR - gloss levels

|   |   |               |
|---|---|---------------|
| resins  | Not Available                           | Not Available |
| dipropylene glycol monomethyl ether               | Unknown mg/m <sup>3</sup> / Unknown ppm | 600 ppm       |
| diethylene glycol monobutyl ether                 | Not Available                           | Not Available |
| triethylamine                                     | 1,000 ppm                               | 200 ppm       |
| bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate    | Not Available                           | Not Available |
| Tinuvin 1130                                      | Not Available                           | Not Available |
| Tinuvin 213                                       | Not Available                           | Not Available |
| methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | Not Available                           | Not Available |

**MATERIAL DATA**

for polyethylene glycols:

For powdered forms:

The polyethylene glycols are extremely low in oral toxicity, are not significantly irritating to the eyes or skin, and are not absorbed through the skin in toxic amounts. vapour pressures are extremely low and inhalation exposure is limited to mists. Based on experimental data and human experience, these substances do not present significant hazards to health in the workplace.

for N-methyl-2-pyrrolidone (NMP):

Reports of skin and eye irritation and chronic headaches have been reported in workers exposed to 1-methyl-2-pyrrolidone. The Australian ES is based on a 10-fold uncertainty factor of the no-observable-adverse-effect level (NOAEL) of 24 ppm where adverse respiratory effects were observed in a 4-week inhalation study in rats.

For trimethyl benzene as mixed isomers (of unstated proportions)

Odour Threshold Value: 2.4 ppm (detection)

Use care in interpreting effects as a single isomer or other isomer mix. Trimethylbenzene is an eye, nose and respiratory irritant. High concentrations cause central nervous system depression.

Exposed workers show CNS changes, asthmatic bronchitis and blood dyscrasias at 60 ppm. The TLV-TWA is thought to be protective against the significant risk of CNS excitation, asthmatic bronchitis and blood dyscrasias associated with exposures above the limit.

Odour Safety Factor (OSF)

OSF=10 (1,2,4-TRIMETHYLBENZENE)

for dipropylene glycol monomethyl ether:

The TLV-TWA and STEL recommendations were thought to be sufficiently low to prevent objectionable irritation and provide a considerable safety factor against CNS impairment. In view of the large dose required to cause weight loss and narcosis in rabbits the skin notation is being reviewed.

Probable minimum concentration that may cause minor nasal irritation is about 35 ppm.

Probable minimum concentration that may cause tolerable eye, throat, and respiratory irritation is about 75 ppm.

Lowest concentration at which vapour is rated tolerable 80 ppm.

Based on these criteria it is possible that an occasional person may find the vapour of dipropylene glycol monomethyl ether intolerable at the recommended 100 ppm TLV.

Dermal absorption of the substance under specific experimental conditions led to narcotic effects and consequent deaths. However, only slight narcotic effects were seen after several hours exposure of rats to

aerosols which wet the fur of animals. Rabbits tolerated dermal application of 3.0 ml/kg per day without effects. A skin designation is thought to be unnecessary by the MAK committee, in contrast with others.

for propylene glycol monomethyl ether (PGME)

Odour Threshold: 10 ppm.

The TLV-TWA is protective against discomfort caused by odour, against eye and skin irritation, and chronic effects (including possible liver and kidney damage).

Individuals exposed to 100 ppm reported a transient unpleasant odour with slight eye irritation after about 1 or 2 hours. At 300 ppm, mild irritation of the eyes and nose developed within 5 minutes; some individuals found the irritation hardly bearable after about an hour. A concentration of 750 ppm was highly irritating. Signs of central nervous system depression developed at 1000 ppm.

Neurological, clinical chemical and general medical examinations showed no other conspicuous toxicity.

Concentrations of the beta-isomer, 2-methoxy-1-propyl acetate are low in commercial grades of PGME and teratogenic effects associated with this isomer are expected to be absent.

Odour Safety Factor(OSF)

OSF=10 (propylene glycol monomethyl ether)

For amorphous crystalline silica (precipitated silicic acid):

Amorphous crystalline silica shows little potential for producing adverse effects on the lung and exposure standards should reflect a particulate of low intrinsic toxicity. Mixtures of amorphous silicas/ diatomaceous earth and crystalline silica should be monitored as if they comprise only the crystalline forms.

The dusts from precipitated silica and silica gel produce little adverse effect on pulmonary functions and are not known to produce significant disease or toxic effect.

IARC has classified silica, amorphous as Group 3: **NOT** classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

Exposed individuals are **NOT** reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class C, D or E.

The Odour Safety Factor (OSF) is defined as:

OSF= Exposure Standard (TWA) ppm/ Odour Threshold Value (OTV) ppm

Classification into classes follows:

Class OSF Description

A 550 Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV-TWA for example) is being reached, even when distracted by working activities

B 26-550 As "A" for 50-90% of persons being distracted

C 1-26 As "A" for less than 50% of persons being distracted

D 0.18-1 10-50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached

E <0.18 As "D" for less than 10% of persons aware of being tested

For ethylene glycol monobutyl ether (2-butoxyethanol)

Odour Threshold Value: 0.10 ppm (detection), 0.35 ppm (recognition)

Although rats appear to be more susceptible than other animals anaemia is not uncommon amongst humans following exposure. The TLV reflects the need to maintain exposures below levels found to cause blood changes in experimental animals. It is concluded that this limit will reduce the significant risk of irritation, haematologic effects and other systemic effects observed in humans and animals exposed to higher vapour concentrations. The toxic effects typical of some other glycol ethers (pancytopenia, testis atrophy and teratogenic effects) are not found with this substance.

Odour Safety Factor (OSF)

OSF=2E2 (2-BUTOXYETHANOL)

For diethylene glycol monobutyl ether:

CEL TWA: 15.5 ppm, 100 mg/m<sup>3</sup>

(CEL = Chemwatch Exposure Limit)

In studies involving the inhalation toxicity of diethylene glycol monobutyl ether, exposure for 6 hours daily at 100 mg/m<sup>3</sup> had no effect. This concentration is in the range of the saturated vapour

## MICROFLOOR - gloss levels

concentration.

Local damage was produced following inhalation of concentrations higher than the saturated vapour concentrations, that is, during inhalation of the aerosol (350 mg/m<sup>3</sup>). Since the only potential effects of inhalation are restricted to local discomfort (in the aerosol concentration range) the substance is classified in category I for the limitation of exposure peaks.

Teratogenicity studies have not revealed prenatal toxic effects at high oral doses and this ether is classified in pregnancy risk group C.

For triethylamine:

Odour Threshold Value: <0.1-0.65 ppm (detection), 0.27-29.0 ppm (recognition)

NOTE: Detector tubes for triethylamine, measuring in excess of 5 ppm, are commercially available.

Exposure at or below the recommended TLV-TWA or STEL is thought to provide worker protection against acute ocular, upper respiratory tract and pulmonary irritation. Nevertheless reports of visual disturbance in workers exposed at concentrations as low as 3 ppm have been cited in literature.

Odour Safety Factor (OSF)

OSF=2.1 (TRIEETHYLAMINE)

## Exposure controls

| Appropriate engineering controls  | <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p> <p>Employers may need to use multiple types of controls to prevent employee overexposure.</p> <p>General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in special circumstances. If risk of overexposure exists, wear approved respirator. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection. Provide adequate ventilation in warehouses and enclosed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.</p>  |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |
|---|--|----------------------|------------|--|-----------------------------|---|----------------------------|--|----------------------------|---|------------------------------|------------------------|------------------------|---|---------------------------------|--|----------------------------------|----------------------------------|-------------------------------|---|
|   | <table border="1"> <thead> <tr> <th>Type of Contaminant:</th> <th>Air Speed:</th> </tr> </thead> <tbody> <tr> <td>solvent, vapours, degreasing etc., evaporating from tank (in still air).</td> <td>0.25-0.5 m/s (50-100 f/min)</td> </tr> <tr> <td>aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)</td> <td>0.5-1 m/s (100-200 f/min.)</td> </tr> <tr> <td>direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)</td> <td>1-2.5 m/s (200-500 f/min.)</td> </tr> <tr> <td>grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion)</td> <td>2.5-10 m/s (500-2000 f/min.)</td> </tr> </tbody> </table> <p>Within each range the appropriate value depends on:</p> <table border="1"> <thead> <tr> <th>Lower end of the range</th> <th>Upper end of the range</th> </tr> </thead> <tbody> <tr> <td>1: Room air currents minimal or favourable to capture</td> <td>1: Disturbing room air currents</td> </tr> <tr> <td>2: Contaminants of low toxicity or of nuisance value only.</td> <td>2: Contaminants of high toxicity</td> </tr> <tr> <td>3: Intermittent, low production.</td> <td>3: High production, heavy use</td> </tr> <tr> <td>4: Large hood or large air mass in motion</td> <td>4: Small hood-local control only</td> </tr> </tbody> </table> <p>Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.</p> | Type of Contaminant: | Air Speed: | solvent, vapours, degreasing etc., evaporating from tank (in still air). | 0.25-0.5 m/s (50-100 f/min) | aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s (100-200 f/min.) | direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) | 1-2.5 m/s (200-500 f/min.) | grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion) | 2.5-10 m/s (500-2000 f/min.) | Lower end of the range | Upper end of the range | 1: Room air currents minimal or favourable to capture | 1: Disturbing room air currents | 2: Contaminants of low toxicity or of nuisance value only. | 2: Contaminants of high toxicity | 3: Intermittent, low production. | 3: High production, heavy use | 4: Large hood or large air mass in motion |
| Type of Contaminant:  | Air Speed:   |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |
| solvent, vapours, degreasing etc., evaporating from tank (in still air).  | 0.25-0.5 m/s (50-100 f/min)  |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |
| aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s (100-200 f/min.)   |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |
| direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)  | 1-2.5 m/s (200-500 f/min.)   |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |
| grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion)   | 2.5-10 m/s (500-2000 f/min.)   |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |
| Lower end of the range  | Upper end of the range   |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |
| 1: Room air currents minimal or favourable to capture   | 1: Disturbing room air currents  |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |
| 2: Contaminants of low toxicity or of nuisance value only.  | 2: Contaminants of high toxicity   |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |
| 3: Intermittent, low production.  | 3: High production, heavy use  |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |
| 4: Large hood or large air mass in motion   | 4: Small hood-local control only   |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |
| Personal protection   |   |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |
| Eye and face protection   | <ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> <li>▶ Chemical goggles.</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</li> </ul>  |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |
| Skin protection   | See Hand protection below  |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |
| Hands/feet protection   | <ul style="list-style-type: none"> <li>▶ Wear chemical protective gloves, e.g. PVC.</li> <li>▶ Wear safety footwear or safety gumboots, e.g. Rubber</li> </ul> <p><b>NOTE:</b></p> <ul style="list-style-type: none"> <li>▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.</li> <li>▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.</li> </ul> <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.</p> <p>Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:</p> <ul style="list-style-type: none"> <li>• frequency and duration of contact,</li> </ul>  |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |

## MICROFLOOR - gloss levels

|                         |  |
|-------------------------|--|
|                         | <ul style="list-style-type: none"> <li>chemical resistance of glove material,</li> <li>glove thickness and</li> <li>dexterity</li> </ul> <p>Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</p> <ul style="list-style-type: none"> <li>When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.</li> <li>Contaminated gloves should be replaced.</li> </ul> <p>For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.</p> <p>It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.</p> <p>Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.</p> <p>Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:</p> <ul style="list-style-type: none"> <li>Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.</li> <li>Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential</li> </ul> <p>Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> |
| <b>Body protection</b>  | See Other protection below   |
| <b>Other protection</b> | <ul style="list-style-type: none"> <li>Overalls.</li> <li>P.V.C. apron.</li> <li>Barrier cream.</li> <li>Skin cleansing cream.</li> <li>Eye wash unit.</li> </ul>  |
| <b>Thermal hazards</b>  | Not Available  |

## Recommended material(s)

## GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

MICROFLOOR - gloss levels

| Material                                    | CPI    |
|---|--------|
| BUTYL                                       | C      |
| NAT+NEOPR+NITRILE                           | C      |
| NATURAL RUBBER                              | C      |
| NEOPRENE                                    | C      |
| NITRILE                                     | C      |
| PE/EVAL/PE                                  | C      |
| PVA   | C      |
| PVC   | C      |
| SARANEX-23                                  | C      |
| VITON                                       | C      |
| ##ethylene glycol monobutyl                 | ether  |
| ##propylene glycol monomethyl ether - alpha | isomer |

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

## Respiratory protection

Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator   |
|------------------------------------|----------------------|----------------------|--------------------------|
| up to 10 x ES                      | AK-AUS P2            | -                    | AK-PAPR-AUS / Class 1 P2 |
| up to 50 x ES                      | -                    | AK-AUS / Class 1 P2  | -                        |
| up to 100 x ES                     | -                    | AK-2 P2              | AK-PAPR-2 P2 ^           |

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content. The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

## Information on basic physical and chemical properties

|                         |   |  |               |
|-------------------------|---|--|---------------|
| <b>Appearance</b>       | Milky white to white low viscosity non-flammable liquid with a characteristic odour; miscible with water. |  |               |
| <b>Physical state</b>   | Liquid  | <b>Relative density (Water = 1)</b>            | 0.98-1.08     |
| <b>Odour</b>            | Not Available   | <b>Partition coefficient n-octanol / water</b> | Not Available |
| <b>Odour threshold</b>  | Not Available   | <b>Auto-ignition temperature (°C)</b>          | Not Available |
| <b>pH (as supplied)</b> | 8-10  | <b>Decomposition temperature</b>               | Not Available |

Continued...

## MICROFLOOR - gloss levels

|   |                |   |                |
|---|----------------|---|----------------|
| <b>Melting point / freezing point (°C)</b>          | Not Available  | <b>Viscosity (cSt)</b>                  | 430-590 223C   |
| <b>Initial boiling point and boiling range (°C)</b> | 104            | <b>Molecular weight (g/mol)</b>         | Not Applicable |
| <b>Flash point (°C)</b>                             | Not Applicable | <b>Taste</b>                            | Not Available  |
| <b>Evaporation rate</b>                             | Not Available  | <b>Explosive properties</b>             | Not Available  |
| <b>Flammability</b>                                 | Not Applicable | <b>Oxidising properties</b>             | Not Available  |
| <b>Upper Explosive Limit (%)</b>                    | Not Available  | <b>Surface Tension (dyn/cm or mN/m)</b> | Not Available  |
| <b>Lower Explosive Limit (%)</b>                    | Not Available  | <b>Volatile Component (%vol)</b>        | 72-81          |
| <b>Vapour pressure (kPa)</b>                        | 2.3 @23C       | <b>Gas group</b>                        | Not Available  |
| <b>Solubility in water (g/L)</b>                    | Miscible       | <b>pH as a solution (1%)</b>            | Not Available  |
| <b>Vapour density (Air = 1)</b>                     | 0.7            | <b>VOC g/L</b>                          | 91-102         |

## SECTION 10 STABILITY AND REACTIVITY

|   |  |
|---|--|
| <b>Reactivity</b>                         | See section 7  |
| <b>Chemical stability</b>                 | <ul style="list-style-type: none"> <li>▶ Unstable in the presence of incompatible materials.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul> |
| <b>Possibility of hazardous reactions</b> | See section 7  |
| <b>Conditions to avoid</b>                | See section 7  |
| <b>Incompatible materials</b>             | See section 7  |
| <b>Hazardous decomposition products</b>   | See section 5  |

## SECTION 11 TOXICOLOGICAL INFORMATION

## Information on toxicological effects

|                     |   |
|---------------------|---|
| <b>Inhaled</b>      | <p>Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo.</p> <p>Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.</p> <p>Central nervous system (CNS) depression may include nonspecific discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal. 51r37?</p>   |
| <b>Ingestion</b>    | <p>Accidental ingestion of the material may be damaging to the health of the individual.</p> <p>Central nervous system (CNS) depression may include nonspecific discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal.</p>  |
| <b>Skin Contact</b> | <p>Limited evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>The material may accentuate any pre-existing dermatitis condition</p> |
| <b>Eye</b>          | <p>Limited evidence exists, or practical experience suggests, that the material may cause eye irritation in a substantial number of individuals and/or is expected to produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.</p>  |
| <b>Chronic</b>      | <p>Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems. There exists limited evidence that shows that skin contact with the material is capable either of inducing a sensitisation reaction in a significant number of individuals, and/or of producing positive response in experimental animals.</p> <p>On the basis, primarily, of animal experiments, concern has been expressed by at least one classification body that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment.</p>   |

|  |   |                                   |
|--|---|-----------------------------------|
| <b>MICROFLOOR - gloss levels</b>           | <b>TOXICITY</b>                                 | <b>IRRITATION</b>                 |
|  | Not Available                                   | Not Available                     |
| <b>dipropylene glycol monomethyl ether</b> | <b>TOXICITY</b>                                 | <b>IRRITATION</b>                 |
|  | dermal (rat) LD50: >19020 mg/kg <sup>[1]</sup>  | Eye (human): 8 mg - mild          |
|  | Oral (rat) LD50: 5135 mg/kg <sup>[2]</sup>      | Eye (rabbit): 500 mg/24hr - mild  |
|  |   | Skin (rabbit): 238 mg - mild      |
|  |   | Skin (rabbit): 500 mg (open)-mild |
| <b>diethylene glycol monobutyl ether</b>   | <b>TOXICITY</b>                                 | <b>IRRITATION</b>                 |
|  | Dermal (rabbit) LD50: 2700 mg/kg <sup>[2]</sup> | Eye (rabbit): 20 mg/24h moderate  |



## MICROFLOOR - gloss levels

|   |  |  |
|---|--|--|
|   | Oral (rat) LD50: 4500 mg/kg <sup>[2]</sup>               | Eye (rabbit): 5 mg - SEVERE                                      |
| triethylamine                                     | <b>TOXICITY</b>  | <b>IRRITATION</b>  |
|   | Dermal (rabbit) LD50: 570 mg/kg <sup>[2]</sup>           | Eye (rabbit): 0.25 mg/24h SEVERE                                 |
|   | Inhalation (rat) LC50: 0.00361025 mg/L1 h <sup>[1]</sup> | Eye(rabbit): 50ppm/30d int SEVERE                                |
|   | Oral (rat) LD50: 460 mg/kg <sup>[1]</sup>                | Skin (rabbit): 365 mg open mild                                  |
| bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate    | <b>TOXICITY</b>  | <b>IRRITATION</b>  |
|   | Oral (rat) LD50: 3100 mg/kg <sup>[2]</sup>               | Not Available  |
| Tinuvin 1130                                      | <b>TOXICITY</b>  | <b>IRRITATION</b>  |
|   | Not Available  | Not Available  |
| Tinuvin 213                                       | <b>TOXICITY</b>  | <b>IRRITATION</b>  |
|   | Not Available  | Skin (guinea pig): Strong sensit.<br>Skin (rabbit): non-irritant |
| methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | <b>TOXICITY</b>  | <b>IRRITATION</b>  |
|   | Not Available  | Not Available  |

**Legend:**

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.\* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

|                           |   |
|---------------------------|---|
| MICROFLOOR - gloss levels | <p>For trimethylbenzenes:</p> <p>Absorption of 1,2,4-trimethylbenzene occurs after oral, inhalation, or dermal exposure. Occupationally, inhalation and dermal exposures are the most important routes of absorption although systemic intoxication from dermal absorption is not likely to occur due to the dermal irritation caused by the chemical prompting quick removal. Following oral administration of the chemical to rats, 62.6% of the dose was recovered as urinary metabolites indicating substantial absorption. 1,2,4-Trimethylbenzene is lipophilic and may accumulate in fat and fatty tissues. In the blood stream, approximately 85% of the chemical is bound to red blood cells. Metabolism occurs by side-chain oxidation to form alcohols and carboxylic acids which are then conjugated with glucuronic acid, glycine, or sulfates for urinary excretion. After a single oral dose to rats of 1200 mg/kg, urinary metabolites consisted of approximately 43.2% glycine, 6.6% glucuronic, and 12.9% sulfuric acid conjugates. The two principle metabolites excreted by rabbits after oral administration of 438 mg/kg/day for 5 days were 2,4-dimethylbenzoic acid and 3,4-dimethylhippuric acid. The major routes of excretion of 1,2,4-trimethylbenzene are exhalation of parent compound and elimination of urinary metabolites. Half-times for urinary metabolites were reported as 9.5 hours for glycine, 22.9 hours for glucuronide, and 37.6 hours for sulfuric acid conjugates.</p> <p><b>Acute Toxicity</b> Direct contact with liquid 1,2,4-trimethylbenzene is irritating to the skin and breathing the vapor is irritating to the respiratory tract causing pneumonitis. Breathing high concentrations of the chemical vapor causes headache, fatigue, and drowsiness. In humans liquid 1,2,4-trimethylbenzene is irritating to the skin and inhalation of vapor causes chemical pneumonitis. High concentrations of vapor (5000-9000 ppm) cause headache, fatigue, and drowsiness. The concentration of 5000 ppm is roughly equivalent to a total of 221 mg/kg assuming a 30 minute exposure period (see end note 1). 2. Animals - Mice exposed to 8130-9140 ppm 1,2,4-trimethylbenzene (no duration given) had loss of righting response and loss of reflexes. Direct dermal contact with the chemical (no species given) causes vasodilation, erythema, and irritation (U.S. EPA). Seven of 10 rats died after an oral dose of 2.5 mL of a mixture of trimethylbenzenes in olive oil (average dose approximately 4.4 g/kg). Rats and mice were exposed by inhalation to a coal tar distillate containing about 70% 1,3,5- and 1,2,4-trimethylbenzene; no pathological changes were noted in either species after exposure to 1800-2000 ppm for up to 48 continuous hours, or in rats after 14 exposures of 8 hours each at the same exposure levels. No effects were reported for rats exposed to a mixture of trimethylbenzenes at 1700 ppm for 10 to 21 days</p> <p><b>Neurotoxicity</b> 1,2,4-Trimethylbenzene depresses the central nervous system. Exposure to solvent mixtures containing the chemical causes headache, fatigue, nervousness, and drowsiness. Occupationally, workers exposed to a solvent containing 50% 1,2,4-trimethylbenzene had nervousness, headaches, drowsiness, and vertigo (U.S. EPA). Headache, fatigue, and drowsiness were reported for workers exposed (no dose given) to paint thinner containing 80% 1,2,4- and 1,3,5-trimethylbenzenes</p> <p>Results of the developmental toxicity study indicate that the C9 fraction caused adverse neurological effects at the highest dose (1500 ppm) tested.</p> <p><b>Subchronic/Chronic Toxicity</b> Long-term exposure to solvents containing 1,2,4-trimethylbenzene may cause nervousness, tension, and bronchitis. Painters that worked for several years with a solvent containing 50% 1,2,4- and 30% 1,3,5-trimethylbenzene showed nervousness, tension and anxiety, asthmatic bronchitis, anemia, and alterations in blood clotting; haematological effects may have been due to trace amounts of benzene</p> <p>Rats given 1,2,4-trimethylbenzene orally at doses of 0.5 or 2.0 g/kg/day, 5 days/week for 4 weeks. All rats exposed to the high dose died and 1 rat in the low dose died (no times given); no other effects were reported. Rats exposed by inhalation to 1700 ppm of a trimethylbenzene isomeric mixture for 4 months had decreased weight gain, lymphopenia and neutrophilia.</p> <p><b>Genotoxicity:</b> Results of mutagenicity testing, indicate that the C9 fraction does not induce gene mutations in prokaryotes (Salmonella typhimurium/mammalian microsome assay); or in mammalian cells in culture (in Chinese hamster ovary cells with and without activation). The C9 fraction does not induce chromosome mutations in Chinese hamster ovary cells with and without activation; does not induce chromosome aberrations in the bone marrow of Sprague-Dawley rats exposed by inhalation (6 hours/day for 5 days); and does not induce sister chromatid exchange in Chinese hamster ovary cells with and without activation.</p> <p><b>Developmental/Reproductive Toxicity:</b> A three-generation reproductive study on the C9 fraction was conducted. CD rats (30/sex/group) were exposed by inhalation to the C9 fraction at concentrations of 0, 100, 500, or 1500 ppm (0, 100, 500, or 1500 mg/kg/day) for 6 hours/day, 5 days/week. There was evidence of parental and reproductive toxicity at all dose levels. Indicators of parental toxicity included reduced body weights, increased salivation, hunched posture, aggressive behavior, and death. Indicators of adverse reproductive system effects included reduced litter size and reduced pup body weight. The LOEL was 100 ppm; a no-observed-effect level was not established. Developmental toxicity, including possible developmental neurotoxicity, was evident in rats in a 3-generation reproductive study</p> <p>No effects on fecundity or fertility occurred in rats treated dermally with up to 0.3 mL/rat/day of a mixture of trimethylbenzenes, 4-6 hours/day, 5 days/week over one generation</p> <p>For C9 aromatics (typically trimethylbenzenes - TMBs)</p> <p><b>Acute Toxicity</b></p> <p>Acute toxicity studies (oral, dermal and inhalation routes of exposure) have been conducted in rats using various solvent products containing predominantly mixed C9 aromatic hydrocarbons (CAS RN 64742-95-6). Inhalation LC50's range from 6,000 to 10,000 mg/m<sup>3</sup> for C9 aromatic naphtha and 18,000 to 24,000 mg/m<sup>3</sup> for 1,2,4 and 1,3,5-TMB, respectively. A rat oral LD50 reported for 1,2,4-TMB is 5 grams/kg bw and a rat dermal LD50 for the C9 aromatic naphtha is &gt;4 ml/kg bw. These data indicate that C9 aromatic solvents show that LD50/LC50 values are greater than limit doses for acute toxicity studies established under OECD test guidelines.</p> <p><b>Irritation and Sensitization</b></p> <p>Several irritation studies, including skin, eye, and lung/respiratory system, have been conducted on members of the category. The results indicate that C9 aromatic hydrocarbon solvents are mildly to moderately irritating to the skin, minimally irritating to the eye, and have the potential to irritate the respiratory tract and cause depression of respiratory rates in mice. Respiratory irritation is a key endpoint in the current occupational exposure limits established for C9</p> |
|---------------------------|---|

## MICROFLOOR - gloss levels

aromatic hydrocarbon solvents and trimethylbenzenes. No evidence of skin sensitization was identified.

#### Repeated Dose Toxicity

**Inhalation:** The results from a subchronic (3 month) neurotoxicity study and a one-year chronic study (6 hr/day, 5 days/week) indicate that effects from inhalation exposure to C9 Aromatic Hydrocarbon Solvents on systemic toxicity are slight. A battery of neurotoxicity and neurobehavioral endpoints were evaluated in the 3-month inhalation study on C9 aromatic naphtha tested at concentrations of 0, 101, 452, or 1320 ppm (0, 500, 2,220, or 6,500 mg/m<sup>3</sup>). In this study, other than a transient weight reduction in the high exposure group (not statistically significant at termination of exposures), no effects were reported on neuropathology or neuro/behavioral parameters. The NOAEL for systemic and/or neurotoxicity was 6,500 mg/m<sup>3</sup>, the highest concentration tested. In an inhalation study of a commercial blend, rats were exposed to C9 aromatic naphtha concentrations of 0, 96, 198, or 373 ppm (0, 470, 970, 1830 mg/m<sup>3</sup>) for 6 hr/day, 5 days/week, for 12 months. Liver and kidney weights were increased in the high exposure group but no accompanying histopathology was observed in these organs. The NOAEL was considered to be the high exposure level of 373 ppm, or 1830 mg/m<sup>3</sup>. In two subchronic rat inhalation studies, both of three months duration, rats were exposed to the individual TMB isomers (1,2,4-and 1,3,5-) to nominal concentrations of 0, 25, 100, or 250 ppm (0, 123, 492, or 1230 mg/m<sup>3</sup>). Respiratory irritation was observed at 492 (100 ppm) and 1230 mg/m<sup>3</sup> (250 ppm) and no systemic toxicity was observed in either study. For both pure isomers, the NOELs are 25 ppm or 123 mg/m<sup>3</sup> for respiratory irritation and 250 ppm or 1230 mg/m<sup>3</sup> for systemic effects.

**Oral:** The C9 aromatic naphtha has not been tested via the oral route of exposure. Individual TMB isomers have been evaluated in a series of repeated-dose oral studies ranging from 14 days to 3 months over a wide range of doses. The effects observed in these studies included increased liver and kidney weights, changes in blood chemistry, increased salivation, and decreased weight gain at higher doses. Organ weight changes appeared to be adaptive as they were not accompanied by histopathological effects. Blood changes appeared sporadic and without pattern. One study reported hyaline droplet nephropathy in male rats at the highest dose (1000 mg/kg bw-day), an effect that is often associated with alpha-2mu-globulin-induced nephropathy and not considered relevant to humans. The doses at which effects were detected were 100 mg/kg-bw day or above (an exception was the pilot 14 day oral study - LOAEL 150 mg/kg bw-day - but the follow up three month study had a LOAEL of 600 mg/kg-bw-day with a NOAEL of 200 mg/kg bw-day). Since effects generally were not severe and could be considered adaptive or spurious, oral exposure does not appear to pose a high toxicity hazard for pure trimethylbenzene isomers.

#### Mutagenicity

**In vitro** genotoxicity testing of a variety of C9 aromatics has been conducted in both bacterial and mammalian cells. In vitro point mutation tests were conducted with *Salmonella typhimurium* and *Escherichia coli* bacterial strains, as well as with cultured mammalian cells such as the Chinese hamster cell ovary cells (HGPRT assay) with and without metabolic activation. In addition, several types of in vitro chromosomal aberration tests have been performed (chromosome aberration frequency in Chinese hamster ovary and lung cells, sister chromatid exchange in CHO cells). Results were negative both with and without metabolic activation for all category members. For the supporting chemical 1,2,3-TMB, a single in vitro chromosome aberration test was weakly positive. In in vivo bone marrow cytogenetics test, rats were exposed to C9 aromatic naphtha at concentrations of 0, 153, 471, or 1540 ppm (0, 750, 2,310, or 7,560 mg/m<sup>3</sup>) 6 hr/day, for 5 days. No evidence of in vivo somatic cell genotoxicity was detected. Based on the cumulative results of these assays, genetic toxicity is unlikely for substances in the C9 Aromatic Hydrocarbon Solvents Category

#### Reproductive and Developmental Toxicity

Results from the three-generation reproduction inhalation study in rats indicate limited effects from C9 aromatic naphtha. In each of three generations (F0, F1 and F2), rats were exposed to High Flash Aromatic Naphtha (CAS RN 64742-95-6) via whole body inhalation at target concentrations of 0, 100, 500, or 1500 ppm (actual mean concentrations throughout the full study period were 0, 103, 495, or 1480 ppm, equivalent to 0, 505, 2430, or 7265 mg/m<sup>3</sup>, respectively). In each generation, both sexes were exposed for 10 weeks prior to and two weeks during mating for 6 hrs/day, 5 days/wks. Female rats in the F0, F1, and F2 generation were then exposed during gestation days 0-20 and lactation days 5-21 for 6 hrs/day, 7 days/wk. The age at exposure initiation differed among generations; F0 rats were exposed starting at 9 weeks of age, F1 exposure began at 5-7 weeks, and F2 exposure began at postnatal day (PND) 22. In the F0 and F1 parental generations, 30 rats/sex/group were exposed and mated. However, in the F2 generation, 40/sex/group were initially exposed due to concerns for toxicity, and 30/sex/group were randomly selected for mating, except that all survivors were used at 1480 ppm. F3 litters were not exposed directly and were sacrificed on lactation day 21.

#### Systemic Effects on Parental Generations:

The F0 males showed statistically and biologically significantly decreased mean body weight by ~15% at 1480 ppm when compared with controls. Seven females died or were sacrificed in extremis at 1480 ppm. The F0 female rats in the 495 ppm exposed group had a 13% decrease in body weight gain when adjusted for initial body weight when compared to controls. The F1 parents at 1480 ppm had statistically significantly decreased mean body weights (by ~13% (females) and 22% (males)), and locomotor activity. F1 parents at 1480 ppm had increased ataxia and mortality (six females). Most F2 parents (70/80) exposed to 1480 ppm died within the first week. The remaining animals survived throughout the rest of the exposure period. At week 4 and continuing through the study, F2 parents at 1480 ppm had statistically significant mean body weights much lower than controls (~33% for males; ~28% for females); body weights at 495 ppm were also reduced significantly (by 13% in males and 15% in females). The male rats in the 495 ppm exposed group had a 12% decrease in body weight gain when adjusted for initial body weight when compared to controls. Based on reduced body weight observed, the overall systemic toxicity LOAEC is 495 ppm (2430 mg/m<sup>3</sup>).

**Reproductive Toxicity-Effects on Parental Generations:** There were no pathological changes noted in the reproductive organs of any animal of the F0, F1, or F2 generation. No effects were reported on sperm morphology, gestational period, number of implantation sites, or post-implantation loss in any generation. Also, there were no statistically or biologically significant differences in any of the reproductive parameters, including: number of mated females, copulatory index, copulatory interval, number of females delivering a litter, number of females delivering a live litter, or male fertility in the F0 or in the F2 generation. Male fertility was statistically significantly reduced at 1480 ppm in the F1 rats. However, male fertility was not affected in the F0 or in the F2 generations; therefore, the biological significance of this change is unknown and may or may not be attributed to the test substance. No reproductive effects were observed in the F0 or F1 dams exposed to 1480 ppm (7265 mg/m<sup>3</sup>). Due to excessive mortality at the highest concentration (1480 ppm, only six dams available) in the F2 generation, a complete evaluation is precluded. However, no clear signs of reproductive toxicity were observed in the F2 generation. Therefore, the reproductive NOAEC is considered 495 ppm (2430 mg/m<sup>3</sup>), which excludes analysis of the highest concentration due to excessive mortality.

**Developmental Toxicity - Effects on Pups:** Because of significant maternal toxicity (including mortality) in dams in all generations at the highest concentration (1480 ppm), effects in offspring at 1480 ppm are not reported here. No significant effects were observed in the F1 and F2 generation offspring at 103 or 495 ppm. However, in F3 offspring, body weights and body weight gain were reduced by ~10-11% compared with controls at 495 ppm for approximately a week (PND 14 through 21). Maternal body weight was also depressed by ~12% throughout the gestational period compared with controls. The overall developmental LOAEC from this study is 495 ppm (2430 mg/m<sup>3</sup>) based on the body weights reductions observed in the F3 offspring.

**Conclusion:** No effects on reproductive parameters were observed at any exposure concentration, although a confident assessment of the group exposed at the highest concentration was not possible. A potential developmental effect (reduction in mean pup weight and weight gain) was observed at a concentration that was also associated with maternal toxicity.

#### DIPROPYLENE GLYCOL MONOMETHYL ETHER

The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

#### DIETHYLENE GLYCOL MONOBUTYL ETHER

For diethylene glycol monoalkyl ethers and their acetates:

This category includes diethylene glycol ethyl ether (DGEE), diethylene glycol propyl ether (DGPE), diethylene glycol butyl ether (DGBE) and diethylene glycol hexyl ether (DGHE) and their acetates.

**Acute toxicity:** There are adequate oral, inhalation and/or dermal toxicity studies on the category members. Oral LD50 values in rats for all category members are all > 3000 mg/kg bw, with values generally decreasing with increasing molecular weight. Four to eight hour acute inhalation toxicity studies were conducted for all category members except DGPE in rats at the highest vapour concentrations achievable. No lethality was observed for any of these materials under these conditions. Dermal LD50 values in rabbits range from 2000 mg/kg bw (DGHE) to 15000 mg/kg bw (DGEEA). Signs of acute toxicity in rodents are consistent with non-specific CNS depression typical of organic solvents in general. All category members are slightly irritating to skin and slightly to moderately irritating to eyes (with the exception of DGHE, which is highly irritating to eyes). Sensitisation tests with DGEE, DGEEA, DGPE, DGBE and DGBEA in animals and/or humans were negative.

**Repeat dose toxicity:** Valid oral studies conducted using DGEE, DGPE, DGBEA, DGHE and the supporting chemical DGBE ranged in duration from 30 days to 2 years. Effects predominantly included kidney and liver toxicity, absolute and/or relative changes in organ weights, and some changes in haematological parameters. All effects were seen at doses greater than 800-1000 mg/kg bw/day from oral or dermal studies; no systemic effects were observed in inhalation studies with less than continuous exposure regimens.

**Mutagenicity:** DGEE, DGEEA, DGBE, DGBEA and DGHE generally tested negative for mutagenicity in *S. typhimurium* strains TA98, TA100, TA1535, TA1537 and TA1538 and DGBEA tested negative in *E. coli* WP2uvrA, with and without metabolic activation. *In vitro* cytogenetic and sister chromatid exchange assays with DGBE and DGHE in Chinese Hamster Ovary Cells with and without metabolic activation and *in vivo* micronucleus or cytogenetic tests with DGEE, DGBE and DGHE in rats and mice were negative, indicating that these diethylene glycol ethers are not likely to be genotoxic.

## MICROFLOOR - gloss levels

|   |  |
|---|--|
|   | <p><b>Reproductive and developmental toxicity:</b> Reliable reproductive toxicity studies on DGEE, DGBE and DGHE show no effect on fertility at the highest oral doses tested (4,400 mg/kg/day for DGEE in the mouse and 1,000 mg/kg/day for DGBE and DGHE in the rat). The dermal NOAEL for reproductive toxicity in rats administered DGBE also was the highest dose tested (2,000 mg/kg/day). Although decreased sperm motility was noted in F1 mice treated with 4,400 mg/kg/day DGEE in drinking water for 14 weeks, sperm concentrations and morphology, histopathology of the testes and fertility were not affected. Results of the majority of adequate repeated dose toxicity studies in which reproductive organs were examined indicate that DGPE and DGBEA do not cause toxicity to reproductive organs (including the testes). Test material-related testicular toxicity was not noted in the majority of the studies with DGEE or DGEEA. Results of the developmental toxicity studies conducted with DGEE, DGBE and DGHE are almost exclusively negative. In these studies, effects on the foetus are generally not observed (even at concentrations that produced maternal toxicity). Exposure to 102 ppm (560 mg/m<sup>3</sup>) DGEE by inhalation (maximal achievable vapour concentration) or 1385 mg/kg/day DGEE by the dermal route during gestation did not cause maternal or developmental toxicity in the rat. Maternal toxicity and teratogenesis were not observed in rabbits receiving up to 1000 mg/kg/day DGBE by the dermal route during gestation; however a transient decrease in body weight was observed, which reversed by Day 21. In the mouse, the only concentration of DGEE tested (3500 mg/kg/day by gavage) caused maternal, but no foetal toxicity. Also, whereas oral administration of 2050 mg/kg/day DGBE (gavage) to the mouse and 1000 mg/kg/day DGHE (dietary) caused maternal toxicity, these doses had no effect on the developing foetus.</p>  |
| <p style="text-align: center;"><b>TRIETHYLAMINE</b></p>   | <p>While it is difficult to generalise about the full range of potential health effects posed by exposure to the many different amine compounds, characterised by those used in the manufacture of polyurethane and polyisocyanurate foams, it is agreed that overexposure to the majority of these materials may cause adverse health effects.</p> <ul style="list-style-type: none"> <li>▶ Many amine-based compounds can induce histamine liberation, which, in turn, can trigger allergic and other physiological effects, including bronchoconstriction or bronchial asthma and rhinitis.</li> <li>▶ Systemic symptoms include headache, nausea, faintness, anxiety, a decrease in blood pressure, tachycardia (rapid heartbeat), itching, erythema (reddening of the skin), urticaria (hives), and facial edema (swelling). Systemic effects (those affecting the body) that are related to the pharmacological action of amines are usually transient.</li> </ul> <p>Typically, there are four routes of possible or potential exposure: inhalation, skin contact, eye contact, and ingestion.</p> <p><b>Inhalation:</b></p> <p>Inhalation of vapors may, depending upon the physical and chemical properties of the specific product and the degree and length of exposure, result in moderate to severe irritation of the tissues of the nose and throat and can irritate the lungs. Products with higher vapour pressures have a greater potential for higher airborne concentrations. This increases the probability of worker exposure. Higher concentrations of certain amines can produce severe respiratory irritation, characterised by nasal discharge, coughing, difficulty in breathing, and chest pains. Chronic exposure via inhalation may cause headache, nausea, vomiting, drowsiness, sore throat, bronchopneumonia, and possible lung damage. Also, repeated and/or prolonged exposure to some amines may result in liver disorders, jaundice, and liver enlargement. Some amines have been shown to cause kidney, blood, and central nervous system disorders in laboratory animal studies.</p> <p>While most polyurethane amine catalysts are not sensitizers, some certain individuals may also become sensitized to amines and may experience respiratory distress, including asthma-like attacks, whenever they are subsequently exposed to even very small amounts of vapor. Once sensitized, these individuals must avoid any further exposure to amines. Although chronic or repeated inhalation of vapor concentrations below hazardous or recommended exposure limits should not ordinarily affect healthy individuals, chronic overexposure may lead to permanent pulmonary injury, including a reduction in lung function, breathlessness, chronic bronchitis, and immunologic lung disease.</p> <p>Inhalation hazards are increased when exposure to amine catalysts occurs in situations that produce aerosols, mists, or heated vapors. Such situations include leaks in fitting or transfer lines. Medical conditions generally aggravated by inhalation exposure include asthma, bronchitis, and emphysema.</p> <p><b>Skin Contact:</b></p> <p>Skin contact with amine catalysts poses a number of concerns. Direct skin contact can cause moderate to severe irritation and injury-i.e., from simple redness and swelling to painful blistering, ulceration, and chemical burns. Repeated or prolonged exposure may also result in severe cumulative dermatitis. Skin contact with some amines may result in allergic sensitization. Sensitized persons should avoid all contact with amine catalysts. Systemic effects resulting from the absorption of the amines through skin exposure may include headaches, nausea, faintness, anxiety, decrease in blood pressure, reddening of the skin, hives, and facial swelling. These symptoms may be related to the pharmacological action of the amines, and they are usually transient.</p> <p><b>Eye Contact:</b></p> <p>Amine catalysts are alkaline in nature and their vapours are irritating to the eyes, even at low concentrations. Direct contact with the liquid amine may cause severe irritation and tissue injury, and the "burning" may lead to blindness. (Contact with solid products may result in mechanical irritation, pain, and corneal injury.) Exposed persons may experience excessive tearing, burning, conjunctivitis, and corneal swelling. The corneal swelling may manifest itself in visual disturbances such as blurred or "foggy" vision with a blue tint ("blue haze") and sometimes a halo phenomenon around lights. These symptoms are transient and usually disappear when exposure ceases. Some individuals may experience this effect even when exposed to concentrations below doses that ordinarily cause respiratory irritation.</p> <p><b>Ingestion:</b></p> <p>The oral toxicity of amine catalysts varies from moderately to very toxic. Some amines can cause severe irritation, ulceration, or burns of the mouth, throat, esophagus, and gastrointestinal tract. Material aspirated (due to vomiting) can damage the bronchial tubes and the lungs. Affected persons also may experience pain in the chest or abdomen, nausea, bleeding of the throat and the gastrointestinal tract, diarrhea, dizziness, drowsiness, thirst, circulatory collapse, coma, and even death.</p> <p><b>Polyurethane Amine Catalysts: Guidelines for Safe Handling and Disposal; Technical Bulletin June 2000</b></p> <p><b>Alliance for Polyurethanes Industry</b></p> <p>Inhalation (human) TCLo: 12mg/m<sup>3</sup>/11W contin. Skin (rabbit)mild</p> |
| <p style="text-align: center;"><b>TINUVIN 213</b></p>   | <p>Inhalation (rat) LC50: &gt; 5.8 mg/l Aerosol Eye (rabbit): non-irritant Ames Test: Non Mutagenic</p>  |
| <p style="text-align: center;"><b>MICROFLOOR - gloss levels &amp; DIPROPYLENE GLYCOL MONOMETHYL ETHER</b></p> | <p>for propylene glycol ethers (PGEs):</p> <p>Typical propylene glycol ethers include propylene glycol n-butyl ether (PnB); dipropylene glycol n-butyl ether (DPnB); dipropylene glycol methyl ether acetate (DPMA); tripropylene glycol methyl ether (TPM).</p> <p>Testing of a wide variety of propylene glycol ethers. Testing of a wide variety of propylene glycol ethers has shown that propylene glycol-based ethers are less toxic than some ethers of the ethylene series. The common toxicities associated with the lower molecular weight homologues of the ethylene series, such as adverse effects on reproductive organs, the developing embryo and fetus, blood (haemolytic effects), or thymus, are not seen with the commercial-grade propylene glycol ethers. In the ethylene series, metabolism of the terminal hydroxyl group produces an alkoxyacetic acid. The reproductive and developmental toxicities of the lower molecular weight homologues in the ethylene series are due specifically to the formation of methoxyacetic and ethoxyacetic acids. Longer chain length homologues in the ethylene series are not associated with the reproductive toxicity but can cause haemolysis in sensitive species, also through formation of an alkoxyacetic acid. The predominant alpha isomer of all the PGEs (thermodynamically favored during manufacture of PGEs) is a secondary alcohol incapable of forming an alkoxypropionic acid. In contrast beta-isomers are able to form the alkoxypropionic acids and these are linked to teratogenic effects (and possibly haemolytic effects). This alpha isomer comprises greater than 95% of the isomeric mixture in the commercial product.</p> <p>Because the alpha isomer cannot form an alkoxypropionic acid, this is the most likely reason for the lack of toxicity shown by the PGEs as distinct from the lower molecular weight ethylene glycol ethers. More importantly, however, very extensive empirical test data show that this class of commercial-grade glycol ether presents a low toxicity hazard. PGEs, whether mono, di- or tripropylene glycol-based (and no matter what the alcohol group), show a very similar pattern of low to non-detectable toxicity of any type at doses or exposure levels greatly exceeding those showing pronounced effects from the ethylene series. One of the primary metabolites of the propylene glycol ethers is propylene glycol, which is of low toxicity and completely metabolised in the body.</p> <p>As a class, the propylene glycol ethers are rapidly absorbed and distributed throughout the body when introduced by inhalation or oral exposure. Dermal absorption is somewhat slower but subsequent distribution is rapid. Most excretion for PGEs is via the urine and expired air. A small portion is excreted in the faeces.</p> <p>As a group PGEs exhibits low acute toxicity by the oral, dermal, and inhalation routes. Rat oral LD50s range from &gt;3,000 mg/kg (PnB) to &gt;5,000 mg/kg (DPMA). Dermal LD50s are all &gt; 2,000 mg/kg (PnB, &amp; DPnB; where no deaths occurred), and ranging up to &gt;15,000 mg/kg (TPM). Inhalation LC50 values were higher than 5,000 mg/m<sup>3</sup> for DPMA (4-hour exposure), and TPM (1-hour exposure). For DPnB the 4-hour LC50 is &gt;2,040 mg/m<sup>3</sup>. For PnB, the 4-hour</p>   |

## MICROFLOOR - gloss levels

|  |   |
|--|---|
|  | <p>LC50 was &gt;651 ppm (&gt;3,412 mg/m<sup>3</sup>), representing the highest practically attainable vapor level. No deaths occurred at these concentrations. PnB and TPM are moderately irritating to eyes while the remaining category members are only slightly irritating to nonirritating. PnB is moderately irritating to skin while the remaining category members are slightly to non-irritating. None are skin sensitizers.</p> <p>In repeated dose studies ranging in duration from 2 to 13 weeks, few adverse effects were found even at high exposure levels and effects that did occur were mild in nature. By the oral route of administration, NOAELs of 350 mg/kg-d (PnB – 13 wk) and 450 mg/kg-d (DPnB – 13 wk) were observed for liver and kidney weight increases (without accompanying histopathology). LOAELs for these two chemicals were 1000 mg/kg-d (highest dose tested).</p> <p>Dermal repeated-dose toxicity tests have been performed for many PGEs. For PnB, no effects were seen in a 13-wk study at doses as high as 1,000 mg/kg-d. A dose of 273 mg/kg-d constituted a LOAEL (increased organ weights without histopathology) in a 13-week dermal study for DPnB. For TPM, increased kidney weights (no histopathology) and transiently decreased body weights were found at a dose of 2,895 mg/kg-d in a 90-day study in rabbits. By inhalation, no effects were observed in 2-week studies in rats at the highest tested concentrations of 3244 mg/m<sup>3</sup> (600 ppm) for PnB and 2,010 mg/m<sup>3</sup> (260 ppm) for DPnB. TPM caused increased liver weights without histopathology by inhalation in a 2-week study at a LOAEL of 360 mg/m<sup>3</sup> (43 ppm). In this study, the highest tested TPM concentration, 1010 mg/m<sup>3</sup> (120 ppm), also caused increased liver weights without accompanying histopathology. Although no repeated-dose studies are available for the oral route for TPM, or for any route for DPMA, it is anticipated that these chemicals would behave similarly to other category members.</p> <p>One and two-generation reproductive toxicity testing has been conducted in mice, rats, and rabbits via the oral or inhalation routes of exposure on PM and PMA. In an inhalation rat study using PM, the NOAEL for parental toxicity is 300 ppm (1106 mg/m<sup>3</sup>) with decreases in body and organ weights occurring at the LOAEL of 1000 ppm (3686 mg/m<sup>3</sup>). For offspring toxicity the NOAEL is 1000 ppm (3686 mg/m<sup>3</sup>), with decreased body weights occurring at 3000 ppm (11058 mg/m<sup>3</sup>). For PMA, the NOAEL for parental and offspring toxicity is 1000 mg/kg/d. In a two generation gavage study in rats. No adverse effects were found on reproductive organs, fertility rates, or other indices commonly monitored in such studies. In addition, there is no evidence from histopathological data from repeated-dose studies for the category members that would indicate that these chemicals would pose a reproductive hazard to human health.</p> <p>In developmental toxicity studies many PGEs have been tested by various routes of exposure and in various species at significant exposure levels and show no frank developmental effects. Due to the rapid hydrolysis of DPMA to DPM, DPMA would not be expected to show teratogenic effects. At high doses where maternal toxicity occurs (e.g., significant body weight loss), an increased incidence of some anomalies such as delayed skeletal ossification or increased 13th ribs, have been reported. Commercially available PGEs showed no teratogenicity.</p> <p>The weight of the evidence indicates that propylene glycol ethers are not likely to be genotoxic. <i>In vitro</i>, negative results have been seen in a number of assays for PnB, DPnB, DPMA and TPM. Positive results were only seen in 3 out of 5 chromosome aberration assays in mammalian cells with DPnB. However, negative results were seen in a mouse micronucleus assay with DPnB and PM. Thus, there is no evidence to suggest these PGEs would be genotoxic <i>in vivo</i>. In a 2-year bioassay on PM, there were no statistically significant increases in tumors in rats and mice.</p> |
| <b>MICROFLOOR - gloss levels &amp; TINUVIN 213 &amp; METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL SEBACATE</b>   | No significant acute toxicological data identified in literature search.  |
| <b>DIPROPYLENE GLYCOL MONOMETHYL ETHER &amp; TRIETHYLAMINE</b>   | Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.  |
| <b>DIPROPYLENE GLYCOL MONOMETHYL ETHER &amp; TRIETHYLAMINE</b>   | The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.  |
| <b>DIETHYLENE GLYCOL MONOBUTYL ETHER &amp; TRIETHYLAMINE</b>   | The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.  |
| <b>BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL)SEBACATE &amp; TINUVIN 1130 &amp; TINUVIN 213 &amp; METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL SEBACATE</b> | The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.  |

|                                   |   |                          |   |
|-----------------------------------|---|--------------------------|---|
| Acute Toxicity                    | ✓ | Carcinogenicity          | ⊘ |
| Skin Irritation/Corrosion         | ✓ | Reproductivity           | ⊘ |
| Serious Eye Damage/Irritation     | ✓ | STOT - Single Exposure   | ⊘ |
| Respiratory or Skin sensitisation | ⊘ | STOT - Repeated Exposure | ⊘ |
| Mutagenicity                      | ⊘ | Aspiration Hazard        | ⊘ |

Legend: ✗ – Data available but does not fill the criteria for classification  
✓ – Data available to make classification  
⊘ – Data Not Available to make classification

## SECTION 12 ECOLOGICAL INFORMATION

## Toxicity

| MICROFLOOR - gloss levels | ENDPOINT      | TEST DURATION (HR) | SPECIES       | VALUE         | SOURCE        |
|---------------------------|---------------|--------------------|---------------|---------------|---------------|
|                           | Not Available | Not Available      | Not Available | Not Available | Not Available |

  

| dipropylene glycol monomethyl ether | ENDPOINT | TEST DURATION (HR) | SPECIES   | VALUE     | SOURCE |
|-------------------------------------|----------|--------------------|-----------|-----------|--------|
|                                     | LC50     | 96                 | Fish      | >1930mg/L | 2      |
|                                     | EC50     | 48                 | Crustacea | 1930mg/L  | 2      |

Continued...

## MICROFLOOR - gloss levels

|   |               |                    |                               |               |               |
|---|---------------|--------------------|-------------------------------|---------------|---------------|
|   | EC50          | 72                 | Algae or other aquatic plants | >969mg/L      | 2             |
|   | NOEC          | 72                 | Algae or other aquatic plants | 969mg/L       | 2             |
| diethylene glycol monobutyl ether                 | ENDPOINT      | TEST DURATION (HR) | SPECIES                       | VALUE         | SOURCE        |
|   | LC50          | 96                 | Fish                          | 1300mg/L      | 4             |
|   | EC50          | 48                 | Crustacea                     | >100mg/L      | 1             |
|   | EC50          | 96                 | Algae or other aquatic plants | >100mg/L      | 1             |
|   | NOEC          | 96                 | Algae or other aquatic plants | >=100mg/L     | 1             |
| triethylamine                                     | ENDPOINT      | TEST DURATION (HR) | SPECIES                       | VALUE         | SOURCE        |
|   | LC50          | 96                 | Fish                          | 36mg/L        | 2             |
|   | EC50          | 48                 | Crustacea                     | 17mg/L        | 2             |
| bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate    | ENDPOINT      | TEST DURATION (HR) | SPECIES                       | VALUE         | SOURCE        |
|   | LC50          | 96                 | Fish                          | =0.34mg/L     | 1             |
| Tinuvin 1130                                      | ENDPOINT      | TEST DURATION (HR) | SPECIES                       | VALUE         | SOURCE        |
|   | Not Available | Not Available      | Not Available                 | Not Available | Not Available |
| Tinuvin 213                                       | ENDPOINT      | TEST DURATION (HR) | SPECIES                       | VALUE         | SOURCE        |
|   | Not Available | Not Available      | Not Available                 | Not Available | Not Available |
| methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | ENDPOINT      | TEST DURATION (HR) | SPECIES                       | VALUE         | SOURCE        |
|   | Not Available | Not Available      | Not Available                 | Not Available | Not Available |

**Legend:**

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

for propylene glycol ethers:

**Environmental fate:**

Most are liquids at room temperature and all are water-soluble.

Typical propylene glycol ethers include propylene glycol n-butyl ether (PnB); dipropylene glycol n-butyl ether (DPnB); dipropylene glycol methyl ether acetate (DPMA); tripropylene glycol methyl ether (TPM)

Environmental fate: Log octanol-water partition coefficients (log Kow's) range from 0.309 for TPM to 1.523 for DPnB. Calculated BCFs range from 1.47 for DPnB to 3.16 for DPMA and TPM, indicating low bioaccumulation. Henry's Law Constants, which indicate propensity to partition from water to air, are low for all category members, ranging from  $5.7 \times 10^{-9}$  atm-m<sup>3</sup>/mole for TPM to  $2.7 \times 10^{-9}$  atm-m<sup>3</sup>/mole for PnB. Fugacity modeling indicates that most propylene glycol ethers are likely to partition roughly equally into the soil and water compartments in the environment with small to negligible amounts remaining in other environmental compartments (air, sediment, and aquatic biota). Propylene glycol ethers are unlikely to persist in the environment. Once in air, the half-life of the category members due to direct reactions with photochemically generated hydroxyl radicals, range from 2.0 hours for TPM to 4.6 hours for PnB. In water, most members of this family are "readily biodegradable" under aerobic conditions. (DPMA degraded within 28 days (and within the specified 10-day window) but only using pre-adapted or "acclimated" inoculum.). In soil, biodegradation is rapid for PM and PMA.

**Ecotoxicity:**

Acute aquatic toxicity testing indicates low toxicity for both ethers and acetates. For ethers, effect concentrations are > 500 mg/L. For acetates, effect concentrations are > 151 mg/L.

For 1,2,4-trimethylbenzene:

Half-life (hr) air : 0.48-16

Half-life (hr) H<sub>2</sub>O surface water : 0.24-672

Half-life (hr) H<sub>2</sub>O ground : 336-1344

Half-life (hr) soil : 168-672

Henry's Pa m<sup>3</sup>/mol: 385-627

Bioaccumulation : not significant

1,2,4-Trimethylbenzene is a volatile organic compound (VOC) substance. As a VOC, 1,2,4-trimethylbenzene can contribute to the formation of photochemical smog in the presence of other VOCs.

**Environmental fate:**

**Transport:** 1,2,4-Trimethylbenzene volatilises rapidly from surface waters as predicted by a Henry's law constant of  $5.18 \times 10^{-3}$  (vapor pressure, 2.03 mm Hg). The volatilisation half-life from a model river is calculated to be 3.4 hours. The chemical also volatilises from soils, however, based on an estimated Koc of 472, moderate adsorption to soils and sediments may occur

**Transformation/Persistence**

**Air** - Degradation of 1,2,4-trimethylbenzene in the atmosphere occurs by reaction with hydroxyl radicals. Reaction also occurs with ozone but very slowly (half life, 8820 days) In the atmosphere, two estimates of the half-life are approximately 6 hours and, in the presence of hydroxyl radicals, 0.5 days

**Soil** - Volatilisation is the major route of removal of 1,2,4-trimethylbenzene from soils; although, biodegradation may also occur. Due to the high volatility of the chemical it is unlikely to accumulate in soil or surface water to toxic concentrations

**Water** - Because of 1,2,4-trimethylbenzene's water solubility and its vapor pressure of 2.03 mm Hg, the chemical will rapidly volatilise from surface waters. Biodegradation of 1,2,4-trimethylbenzene occurred with inoculums from both seawater and ground water. Various strains of Pseudomonas can biodegrade 1,2,4-trimethylbenzene.

**Biota** - The estimated bioconcentration factor (439) and high volatility of 1,2,4-trimethylbenzene indicates that bioaccumulation of the chemical will not be significant

**Ecotoxicity:**

Fish LC50 (96 h): fathead minnow 7.72 mg/l

No stress was observed in Oncorhynchus mykiss (rainbow trout, fingerling) or Petromyzon marinus (sea lamprey, larvae) at 5 mg/L for 24 hours

Daphnia magna EC50 (48 h): 3.61 mg/l

Cancer magister (dungeness crab) LC50 996 h): 5.1 mg/l

1,2,4-Trimethylbenzene has moderate acute toxicity to aquatic organisms; acute toxicity values fall within the range of greater than 1 mg/L and 100 mg/L. LC50 values for specific aquatic organisms range from approximately 5 to 8 mg/L which is orders of magnitude greater than any measured concentration in seawater (0.002 - 0.54 microgram/L). The high concentrations required to induce toxicity in laboratory animals are not likely to be reached in the environment.

Within an aromatic series, acute toxicity increases with increasing alkyl substitution on the aromatic nucleus. For example, there is an increase in toxicity as alkylation of the naphthalene structure increases. The order of most toxic to least in a study using grass shrimp (Palaemonetes pugio) and brown shrimp (Penaeus aztecus) was dimethylnaphthalenes > methylnaphthalenes > naphthalenes.

Studies conclude that the toxicity of an oil appears to be a function of its di-aromatic and tri-aromatic hydrocarbons, which includes three-ring hydrocarbons such as phenanthrene.

The heavier (4-, 5-, and 6-ring) PAHs are more persistent than the lighter (2- and 3-ring) PAHs and tend to have greater carcinogenic and other chronic impact potential. PAHs in general are more frequently associated with chronic risks. These risks include cancer and often are the result of exposures to complex mixtures of chronic-risk aromatics (such as PAHs, alkyl PAHs, benzenes, and alkyl benzenes), rather than exposures to low levels of a single compound.

Anthracene is a phototoxic PAH. UV light greatly increases the toxicity of anthracene to bluegill sunfish. Benchmarks developed in the absence of UV light may be under-protective, and biological resources in strong sunlight are at more risk than those that are not.

For C9 aromatics (typically trimethylbenzene - TMBs)

Chemicals in this category possess properties indicating a hazard for the environment (acute toxicity for fish, invertebrates, and algae from 1 to 10 mg/L). Category members are readily biodegradable, except 1,3,5-trimethylbenzene (CAS RN 108-67-8). Category members are not expected to be bioaccumulative.

Environmental Fate:

In the air, category member constituents have the potential to rapidly degrade through indirect photolytic processes mediated primarily by hydroxyl radicals with calculated degradation half-lives ranging from 0.54 to 2.81 days (based on a 12-hour day and a hydroxyl radical concentration of  $5 \times 10^{-5}$ ). Aqueous photolysis and hydrolysis will not contribute to the transformation of category chemical constituents in aquatic environments because they are either poorly reactive or not susceptible to these reactions.

Results of the Mackay Level I environmental distribution model show that chemical constituents of C9 Aromatic Hydrocarbon Solvents Category members have the potential to partition to air (96.8 to 98.9%), with a negligible amount partitioning to water (0.2 to 0.6%) and soil (0.9 to 2.7%). In comparison, Level III modeling indicates that category members partition primarily to soil (66.3 to 79.6%) and water (17.8 to 25.0%) compartments rather than air (2.4 to 8.4%) when an equal emission rate (1000 kg/hr) is assumed to each of the air, water, and soil compartments. When release (1000 kg/hr) is modeled only to either the air, water, or soil compartment, constituents are indicated in the modeling to partition primarily (>94%) to the compartment to which they are emitted as advection and degradation influence constituent concentration in compartments to which constituents are not released. Solvent naphtha, (pet.), light aromatic (CAS RN 64742-95-6), 1,2,4-trimethylbenzene (CAS RN 95-63-6), and 1-ethyl-3-methylbenzene (CAS RN 620-14-4) were determined to be readily biodegradable based on the studies that used the TG OECD 301F (the latter substance is used to characterize the potential biodegradability of the category member, ethylmethylbenzene (CAS RN 25550-14-5)). These three substances exceed 60% biodegradation in 28 days and met the 10-day window criterion for ready biodegradation. In comparison 1,3,5-trimethylbenzene (CAS RN 108-67-8) was not readily biodegradable. It achieved 42% biodegradation after 28 days and 60% biodegradation after 39 days. The result for the multi-constituent substance (CAS RN 64742-95-6), a UVCB, characterizes the biodegradability of that substance as a whole, but it does not suggest that each constituent is equally biodegradable. As with all ready biodegradation test guidelines, the test system and study design used with these substances (OECD TG 301F) is not capable of distinguishing the relative contribution of the substances' constituents to the total biodegradation measured.

Based on Henry's Law constants (HLCs) representing a potential to volatilize from water that range from 590 to 1000 Pa-m<sup>3</sup>/mole, the potential to volatilize from surface waters for chemicals in the C9 Aromatic Hydrocarbon Solvents Category is expected to be high.

Based on the measured bioconcentration factors that range from 23 to 342 for 1,2,4-trimethylbenzene and 1,3,5-trimethylbenzene, the category members are not expected to be bioaccumulative.

Ecotoxicity

Acute toxicity values used to characterize this category for fish (LL50; LC50) and invertebrates (EL50; EC50) range from 3.5 to 9.2 mg/L, based on measured data. For algae, one study for a category member (CAS RN 64742-95-6) resulted in a 72-hr EC50 of 2.4 mg/L (biomass) and 2.7 mg/L (growth rate) based on measured concentrations.

The algal 72-hour NOEC (no observed effect concentration) for biomass and growth rate is 1.3 mg/L, based on mean measured concentrations. A 21-day Daphnia magna reproduction study with 1,3,5-trimethylbenzene (CAS RN 108-67-8) resulted in a NOEC value of 0.4 mg/L, based on a minimum measured value.

for UV filters:

UV filters have been detected in surface water, wastewater and fish, and some of them are estrogenic in fish. At present, little is known about their additional hormonal activities in different hormonal receptor systems despite their increasing use and environmental persistence. Besides estrogenic activity, UV filters may have additional activities, both agonistic and antagonistic in aquatic organisms.

Systematic analysis of the oestrogenic, antioestrogenic, androgenic, and antiandrogenic activity was conducted using 18 UV filters and one metabolite *in vitro* at non-cytotoxic concentrations with recombinant yeast systems carrying either a human estrogen (hER) or androgen receptor (hAR). All 19 compounds elicited hormonal activities, surprisingly most of them multiple activities. Ten UV-filters having agonistic effects towards the hER. Surprisingly, six UV filters with androgenic activities and many of them having pronounced antioestrogenic and antiandrogenic activities. Seventeen compounds inhibited 4,5-dihydrotestosterone activity in the hAR assay, while 14 compounds inhibited oestradiol activity in the hER assay, indicating antiandrogenic and antiestrogenic activity, respectively. In particular, the antiandrogenic activities of phenyl- and benzyl salicylate, benzophenone-1 and -2, and of 4-hydroxybenzophenone were higher than that of flutamide, a known hAR antagonist.

Although most of the UV filters exert hormonal effects at concentrations that are orders of magnitude higher than in the environment, wide distribution and exposure to UV filter mixtures may have environmental consequences due to additive effects. The UV filters 4-methylbenzylidene camphor, benzophenone-3, benzophenone-4, octyl methoxycinnamate, octocrylene and homosalate that repeatedly were detected in the aquatic environment, may contribute with their multiple hormonal activities in a complex manner to the mixture of endocrine disrupting chemicals already present in surface water and fish. For most of the UV filters with multiple hormonal activities residues in the aquatic environment and in biota are not yet known, and therefore their environmental relevance remains elusive. The fact that all 18 UV filters and one metabolite showed receptor ligand binding via transactivation – surprisingly most of them multiple bindings – reveals a complex picture of the hormonal activities of UV filters.

Petra Kunz and Karl Fent: Aquatic Toxicology Vol 79 pp 305-324 October 2006

**DO NOT discharge into sewer or waterways.**

### Persistence and degradability

| Ingredient                          | Persistence: Water/Soil | Persistence: Air |
|-------------------------------------|-------------------------|------------------|
| dipropylene glycol monomethyl ether | HIGH                    | HIGH             |
| diethylene glycol monobutyl ether   | LOW                     | LOW              |
| triethylamine                       | HIGH                    | HIGH             |

### Bioaccumulative potential

| Ingredient                          | Bioaccumulation  |
|-------------------------------------|------------------|
| dipropylene glycol monomethyl ether | LOW (BCF = 100)  |
| diethylene glycol monobutyl ether   | LOW (BCF = 0.46) |
| triethylamine                       | LOW (BCF = 7.45) |

### Mobility in soil

| Ingredient                          | Mobility          |
|-------------------------------------|-------------------|
| dipropylene glycol monomethyl ether | LOW (KOC = 10)    |
| diethylene glycol monobutyl ether   | LOW (KOC = 10)    |
| triethylamine                       | LOW (KOC = 107.2) |

## SECTION 13 DISPOSAL CONSIDERATIONS

**Waste treatment methods**

|                                     |  |
|-------------------------------------|--|
| <b>Product / Packaging disposal</b> | <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A Hierarchy of Controls seems to be common - the user should investigate:</p> <ul style="list-style-type: none"> <li>▶ Reduction</li> <li>▶ Reuse</li> <li>▶ Recycling</li> <li>▶ Disposal (if all else fails)</li> </ul> <p>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.</p> <ul style="list-style-type: none"> <li>▶ <b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Where in doubt contact the responsible authority.</li> <li>▶ Recycle wherever possible.</li> <li>▶ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.</li> <li>▶ Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or incineration in a licensed apparatus (after admixture with suitable combustible material).</li> <li>▶ Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.</li> </ul> |
|-------------------------------------|--|

Ensure that the disposal of material is carried out in accordance with Hazardous Substances (Disposal) Regulations 2001.

**SECTION 14 TRANSPORT INFORMATION****Labels Required**

|                         |                |
|-------------------------|----------------|
| <b>Marine Pollutant</b> | NO             |
| <b>HAZCHEM</b>          | Not Applicable |

**Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Transport in bulk according to Annex II of MARPOL and the IBC code**

Not Applicable

**SECTION 15 REGULATORY INFORMATION****Safety, health and environmental regulations / legislation specific for the substance or mixture**

This substance is to be managed using the conditions specified in an applicable Group Standard

| HSR Number | Group Standard   |
|------------|--|
| HSR002624  | N.O.S. (Subsidiary Hazard) Group Standard 2006   |
| HSR002535  | Compressed Gas Mixtures (Subsidiary Hazard) Group Standard 2006  |
| HSR002596  | Laboratory Chemicals and Reagent Kits Group Standard 2006  |
| HSR002530  | Cleaning Products (Subsidiary Hazard) Group Standard 2006  |
| HSR002585  | Fuel Additives (Subsidiary Hazard) Group Standard 2006   |
| HSR002519  | Aerosols (Subsidiary Hazard) Group Standard 2006   |
| HSR002521  | Animal Nutritional and Animal Care Products Group Standard 2006  |
| HSR002606  | Lubricants, Lubricant Additives, Coolants and Anti-freeze Agents (Subsidiary Hazard) Group Standard 2006 |
| HSR002644  | Polymers (Subsidiary Hazard) Group Standard 2006   |
| HSR002647  | Reagent Kits Group Standard 2006   |
| HSR002612  | Metal Industry Products (Subsidiary Hazard) Group Standard 2006  |
| HSR002670  | Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2006                                  |
| HSR002503  | Additives, Process Chemicals and Raw Materials (Subsidiary Hazard) Group Standard 2006                   |
| HSR002638  | Photographic Chemicals (Subsidiary Hazard) Group Standard 2006   |
| HSR002565  | Embalming Products (Subsidiary Hazard) Group Standard 2006   |
| HSR002578  | Food Additives and Fragrance Materials (Subsidiary Hazard) Group Standard 2006                           |
| HSR002558  | Dental Products (Subsidiary Hazard) Group Standard 2006  |
| HSR002684  | Water Treatment Chemicals (Subsidiary Hazard) Group Standard 2006  |
| HSR002573  | Fire Fighting Chemicals Group Standard 2006  |
| HSR100425  | Pharmaceutical Active Ingredients Group Standard 2010  |
| HSR002600  | Leather and Textile Products (Subsidiary Hazard) Group Standard 2006                                     |
| HSR002605  | Lubricants (Low Hazard) Group Standard 2006  |
| HSR002571  | Fertilisers (Subsidiary Hazard) Group Standard 2006  |
| HSR002648  | Refining Catalysts Group Standard 2006   |

## MICROFLOOR - gloss levels

|           |   |
|-----------|---|
| HSR002653 | Solvents (Subsidiary Hazard) Group Standard 2006                                    |
| HSR002544 | Construction Products (Subsidiary Hazard) Group Standard 2006                       |
| HSR002549 | Corrosion Inhibitors (Subsidiary Hazard) Group Standard 2006                        |
| HSR002552 | Cosmetic Products Group Standard 2006   |
| HSR100757 | Veterinary Medicine (Limited Pack Size, Finished Dose) Standard 2012                |
| HSR100758 | Veterinary Medicines (Non-dispersive Closed System Application) Group Standard 2012 |
| HSR100628 | Straight-chained Lepidopteran Sex Pheromone Group Standard 2012                     |
| HSR100580 | Tattoo and Permanent Makeup Substances Group Standard 2011                          |

**DIPROPYLENE GLYCOL MONOMETHYL ETHER(34590-94-8) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals  
New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

**DIETHYLENE GLYCOL MONOBUTYL ETHER(112-34-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Inventory of Chemicals (NZIoC)

**TRIETHYLAMINE(121-44-8) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals  
New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

**BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL)SEBACATE(41556-26-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Inventory of Chemicals (NZIoC)

**TINUVIN 1130(104810-47-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Inventory of Chemicals (NZIoC)

**TINUVIN 213(104810-48-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Inventory of Chemicals (NZIoC)

**METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL SEBACATE(82919-37-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Inventory of Chemicals (NZIoC)

**Location Test Certificate**

Subject to Regulation 55 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations, a location test certificate is required when quantity greater than or equal to those indicated below are present.

| Hazard Class   | Quantity beyond which controls apply for closed containers | Quantity beyond which controls apply when use occurring in open containers |
|----------------|--|--|
| Not Applicable | Not Applicable   | Not Applicable   |

**Approved Handler**

Subject to Regulation 56 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations and Regulation 9 of the Hazardous Substances (Classes 6, 8, and 9 Controls) Regulations, the substance must be under the personal control of an Approved Handler when present in a quantity greater than or equal to those indicated below.

| Class of substance | Quantities     |
|--------------------|----------------|
| Not Applicable     | Not Applicable |

Refer Group Standards for further information

**Tracking Requirements**

Not Applicable

| National Inventory            | Status  |
|-------------------------------|---|
| Australia - AICS              | Y   |
| Canada - DSL                  | Y   |
| Canada - NDSL                 | N (triethylamine; diethylene glycol monobutyl ether; bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate; Tinuvin 213; dipropylene glycol monomethyl ether; Tinuvin 1130; methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate) |
| China - IECSC                 | Y   |
| Europe - EINEC / ELINCS / NLP | N (Tinuvin 213; Tinuvin 1130)   |
| Japan - ENCS                  | N (diethylene glycol monobutyl ether; Tinuvin 213; Tinuvin 1130)  |
| Korea - KECI                  | Y   |
| New Zealand - NZIoC           | Y   |
| Philippines - PICCS           | Y   |
| USA - TSCA                    | Y   |
| <b>Legend:</b>                | Y = All ingredients are on the inventory<br>N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)                                |



## SECTION 16 OTHER INFORMATION

### Other information

#### Ingredients with multiple cas numbers

| Name                                | CAS No   |
|-------------------------------------|--|
| dipropylene glycol monomethyl ether | 34590-94-8, 12002-25-4, 112388-78-0, 104512-57-4, 83730-60-3, 112-28-7, 13429-07-7, 20324-32-7, 13588-28-8, 55956-21-3 |

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

#### Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average  
PC—STEL: Permissible Concentration-Short Term Exposure Limit  
IARC: International Agency for Research on Cancer  
ACGIH: American Conference of Governmental Industrial Hygienists  
STEL: Short Term Exposure Limit  
TEEL: Temporary Emergency Exposure Limit.  
IDLH: Immediately Dangerous to Life or Health Concentrations  
OSF: Odour Safety Factor  
NOAEL :No Observed Adverse Effect Level  
LOAEL: Lowest Observed Adverse Effect Level  
TLV: Threshold Limit Value  
LOD: Limit Of Detection  
OTV: Odour Threshold Value  
BCF: BioConcentration Factors  
BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.