



QUANTUM

TIMBER FINISHES



Environmentally Sustainable, Environmentally Responsible.

QTHANE

A solvent based, single pack, clear polyurethane floor finish.

Advantages

- A hard durable coating.
- Good resistance to household chemicals.

Typical Applications

Interior timber floors and trims and furniture.

Coverage

- 12m² per litre.

Application Method

By brush, roller or applicator.

Good preparation is key to a professional looking, long lasting finish:

Uncoated timber:

- Ensure the surface is free of dirt, grease and loose material.
- Fill holes with wood filler and allow to dry.
- Sand to a smooth finish in the direction of the grain, remove dust.
- If required apply AQUASTAIN in the colour of your choice.
- Applying a minimum of 2 coats of QTHANE, sanding between coats with 240 grit paper.

Previously coated timber:

- Sand off all old coating before applying QTHANE. Follow directions above.

Note: Always test recycled timber for adhesion prior to full application.

Specifications	Heat/Temperature	Do not apply if temperature is below 15°C or above 30°C.
	Drying	Touch Dry – 4 hours Light Foot Traffic – 24 hours Recoat – 12 hours Normal Traffic – 72 hours <i>In cooler or humid conditions drying times will be longer.</i>

QTHANE



A solvent based, single pack, clear polyurethane floor finish.

Properties	Colour	Clear.
	Finish	Satin & Gloss.
	Thinner	MIROSOL 1228.
	Pack Sizes	4L, 10L.
	Product Code	4400.
	Clean Up	MIROSOL 1228.

Health & Safety

Before handling, refer to the Safety Data Sheet (SDS) for health and safety information. Ensure that all people using this product have read and understood this data sheet, the associated SDS and packaging label before using this product.
