



# QUANTUM

## TIMBER FINISHES



*Environmentally Sustainable, Environmentally Responsible.*

## TIMBRE PLUS Interior

A unique solvent free, oil based coating. It has outstanding adhesion and toughness, and dries to a scuff resistant finish.

### Advantages

- Environmentally responsible - made from bio based, ecologically sustainable products.
- Non-toxic, low odour, low allergenic.
- A tough, scuff resistant finish.
- May be tinted to transparent or solid opaque stain colours.
- Complies with the Green Building Council Australia: Green Star – Office Design v3 & Office As Built, Table IEQ-13.1 Maximum TVOC Content Limits for Paints, Varnishes and Protective Coatings.

### Typical Applications

Interior timber such as Cedar, Cypress, Oregon, Australian hardwoods and pine lining boards. Ideal for wall panelling, furniture, doors, joinery and other interior woodwork.

### Coverage

- 7 - 10 m<sup>2</sup> per litre depending upon the porosity of the timber, the first coat may use more.

### Application Method

**By brush, roller or spray.**

Good preparation is key to a professional looking, long lasting finish:

1. Ensure the surface is clean, dry and free from all dirt, dust, grease and grime.
2. For best results, flood-coat the timber to achieve maximum penetration on the first coat. Allow to dry.
3. Apply another 1-2 coats as required.
4. Spraying: Airless spray recommended. Use a 0.33 to 0.38mm (13 – 15 thou) orifice, 10cm fan (dependent on job) with a regulated pump pressure of 350-400 kPa (50 – 55 psi) tip pressure. Back brushing is recommended to achieve an even finish. Use normal protection i.e. mask, overalls. Watch your overspray. Wash off with soap and water before it dries.

Note: Stir thoroughly before using.

# TIMBRE PLUS Interior



A unique solvent free, oil based coating. It has outstanding adhesion and toughness, and dries to a scuff resistant finish.

<b>Specifications</b>	<b>Heat/Temperature</b>	Do not apply if temperature is below 15°C or above 30°C.
	<b>Drying</b>	Touch Dry – 2-4 hours                      Recoat – 6 hours <i>In cooler or humid conditions drying times will be longer.</i>
<b>Properties</b>	<b>Colour</b>	Clear or tinted with Quantum Transparent and Solid Opaque Stains.
	<b>Finish</b>	Low Sheen.
	<b>VOC Level</b>	<23g/L.
	<b>Thinner</b>	Not required.
	<b>Pack Sizes</b>	1L, 4L, 10L, 20L.
	<b>Product Code</b>	4330.
	<b>Clean Up</b>	Water clean-up.

## Health & Safety

Before handling, refer to the Safety Data Sheet (SDS) for health and safety information. Ensure that all people using this product have read and understood this data sheet, the associated SDS and packaging label before using this product.